
KEMET Part Number: F5ADC3220Z3C5K Not for New Design

(5ADC3220Z3C5K)



F5A, Film, Metallized Polyester, Varistor/Capacitor, 0.22 uF, 10%, 63 VDC, 100°C, Lead Spacing = 5mm



General Information		
Series:	F5A	
Dielectric:	Metallized Polyester	
Style:	Radial	
Features:	EMI-RFI suppressors for DC	
	motors	
RoHS:	Yes	
Lead:	Wire Leads	
Miscellaneous:	The Rated Voltage Decreases	
	2%/C Between +100C And	
	+125C. Varistor= 68 VDC	

Dimensions	
L	7.4mm MAX
Н	9.6mm MAX
Т	4.6mm MAX
S	5mm +/-0.4mm
LL	17mm +1/-2mm
F	0.6mm +/-0.05mm

Packaging Specifications	
Packaging:	Bulk, Bag
Packaging Quantity:	2000

Specifications		
Capacitance:	0.22 uF	
Capacitance Tolerance:	10%	
Voltage DC:	63 VDC, 32 VDC (125C)	
Temperature Range:	-55/+125°C	
Rated Temperature:	100°C	
Dissipation Factor:	1.00% 1kHz	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.





单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)