


KEMET Part Number: MDC15565J100B55P4TUBE
(F154AB565J100T)

MDC, Film, Metallized Polyester, 5.6 uF, 5%, 63 VAC, 100 VDC, 85°C



Dimensions

L	12.2mm +/-0.2mm
W	16.5mm +/-0.2mm
T	6.05mm +/-0.2mm
F	0.5mm +/-0.05mm

Packaging Specifications

Packaging:	Bulk, Tube
Packaging Quantity:	39

General Information

Series:	MDC
Dielectric:	Metallized Polyester
Style:	Dual-In-Line
RoHS:	Yes
Lead:	L Leads

Specifications

Capacitance:	5.6 uF
Capacitance Tolerance:	5%
Voltage AC:	63 VAC
Voltage DC:	100 VDC
Temperature Range:	-55/+125C
Rated Temperature:	85°C
Dissipation Factor:	0.8% 1kHz, 1.5% 10kHz
Insulation Resistance:	892.9 MOhms
Inductance:	4 nH

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)