


ALS33, Aluminum Electrolytic, 390 uF, 20%, 450 VDC, -40/+85°C



General Information	
Series:	ALS33
Dielectric:	Aluminum Electrolytic
Description:	Screw Terminal, Aluminum Electrolytic
RoHS:	Yes
Mounting:	Stud
AEC-Q200:	No
Notes:	Add 0.4mm To D (1.1mm When D = 88.9) And 1.1mm To L For Sleeving. MS (MxH) = M8x12

Dimensions	
D	34.9mm +/-0.8mm
L	79.4mm +/-1.6mm
T	7.14mm +/-0.5mm
S	12.8mm +/-0.5mm
DT	8mm +/-0.8mm
LT	87.5mm +/-1mm
TD	10mm MIN
V	8mm NOM

Specifications	
Capacitance:	390 uF
Capacitance Tolerance:	20%
Voltage DC:	450 VDC, 495 VDC (Surge)
Temperature Range:	-40/+85°C
Rated Temperature:	85°C
Life:	11000 Hrs (Rated Voltage And Ripple Current At 85C), 22000 Hrs (Rated Voltage At 85C)
Resistance:	265 mOhms (120Hz 25C), 149 mOhms (20kHz 25C)
Ripple Current:	3.4 Amps (120Hz 85C), 7.4 Amps (20kHz 85C)
Leakage Current:	1053 uA (5min 20°C)

Packaging Specifications	
Weight:	114 g
Packaging:	Bulk, Box

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)