
## **KEMET Part Number: C2220C472KGRACTU**

(C2220C472KGRAC7800)



SMD Comm X7R HV, Ceramic, 4700 pF, 10%, 2000 VDC, X7R, SMD, MLCC, High Voltage, Temperature Stable, 2220



Dimensions		
L	5.7mm +/-0.4mm	
W	5mm +/-0.4mm	
Т	1.6mm +/-0.20mm	
В	0.6mm +/-0.35mm	

Packaging Specifications		
Packaging:	T&R, 180mm, Plastic Tape	
Packaging Quantity:	1000	

General Information	
Series:	SMD Comm X7R HV
Style:	SMD Chip
Description:	SMD, MLCC, High Voltage, Temperature Stable
Features:	High Voltage
RoHS:	Yes
Termination:	Tin
Marking:	No
AEC-Q200:	No
Miscellaneous:	Note: Referee time for X7R dielectric for this part number is 1000 hours
Chip Size:	2220
Shelf Life:	78 Weeks
MSL:	1

Specifications		
Capacitance:	4700 pF, 1kHz 1.0Vrms	
Capacitance Tolerance:	10%	
Voltage DC:	2000 VDC	
Dielectric Withstanding Voltage:	2400 VDC	
Temperature Range:	-55/+125°C	
Temperature Coefficient:	X7R	
Capacitance Change with Reference to +25°C and 0 VDC Applied (TCC):	15%, 1kHz 1.0Vrms	
Dissipation Factor:	2.50% 1kHz 1.0Vrms	
Aging Rate:	3% Loss/Decade Hour	
Insulation Resistance:	100 GOhms	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.



单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)