

KEMET Part Number: HT08DB225KN
(HT08DB225K, HT08DW225KN)

HTHP LDD Indust X7R HT200C, Ceramic, 2.2 uF, 10%, 200 VDC, X7R, Commercial, High Temperature, Lead Spacing = 10.16mm



Dimensions

Dimension	Value
L	12.7mm MAX
H	12.7mm MAX
T	6.35mm MAX
S	10.16mm +/-0.76mm
LL	31.75mm MIN
F	0.635mm NOM

Packaging Specifications

Packaging:	Bulk, Bag
Packaging Quantity:	1

General Information

Series:	HTHP LDD Indust X7R HT200C
Style:	Radial
Description:	Commercial, High Temperature
Features:	Commercial
RoHS:	Yes
Termination:	Nickel
Failure Rate:	N/A
AEC-Q200:	No

Specifications

Capacitance:	2.2 uF
Capacitance Tolerance:	10%
Voltage DC:	200 VDC
Dielectric Withstanding Voltage:	500 VDC
Temperature Range:	-55/+200°C
Temperature Coefficient:	X7R
Dissipation Factor:	2.50%
Insulation Resistance:	454.545 MOhms

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)