
KEMET Part Number: MMC7.3822K250K31BULK Not for New Design

(F160SG822K250A)



MMC/F160, Film, Metallized Polyester, General Purpose, 8200 pF, 10%, 160 VAC, 250 VDC, 100°C, 2824, 2.5mm



RoHS: Miscellaneous: Notes:

Note: '()' correspond to the letters used in the product bulletin

Dimensions		
Chip Size	2824	
L	7.3mm +/-0.2mm	
W	6mm +/-0.2mm	
Т	2.5mm +/-0.2mm	
F	0.5mm NOM	

Packaging Specifications		
Packaging:	Bulk, Bag	
Packaging Quantity:	2000	

Specifications		
Capacitance:	8200 pF	
Capacitance Tolerance:	10%	
Voltage AC:	160 VAC	
Voltage DC:	250 VDC	
Temperature Range:	-55/+100C	
Rated Temperature:	100°C	
Dissipation Factor:	0.80% 1kHz, 1.20% 10kHz, 2.50% 100kHz	
Insulation Resistance:	15 GOhms	
Max dV/dt:	40 V/us	

General Information

MMC/F160

SMD Chip

Yes

F161

Metallized Polyester

Not For New Design

Not For New Design. Use Series

Series:

Style:

Dielectric:

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.





单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)