
KEMET Part Number: MDK10334K400A58P7TUBE

(F687AA334K400T)



MDK/F68, Film, Metallized Polyester, Dual-In-Line, 0.33 uF, 10%, 200 VAC, 400 VDC, 85°C, 10mm



General Information		
Series:	MDK/F68	
Dielectric:	Metallized Polyester	
Style:	Dual-In-Line	
RoHS:	Yes	
Lead:	Wire Leads	
AEC-Q200:	No	

Dimensions	
L	23mm +/-0.2mm
L2	3.88mm MAX
W	12.7mm +/-0.2mm
Н	11mm +/-0.2mm
H1	14.2mm +1mm
S	10mm +/-0.2mm
S1	2.54mm +/-0.2mm
S2	15.24mm +/-0.2mm
LL	3.2mm +1mm
F	0.5mm +/-0.05mm
E	0.2mm MAX
G	0.3mm MAX
Х	0.35mm +/-0.05mm

Specifications	
Capacitance:	0.33 uF
Capacitance Tolerance:	10%
Voltage AC:	200 VAC
Voltage DC:	400 VDC
Temperature Range:	-55/+125°C
Rated Temperature:	85°C
Dissipation Factor:	0.80% 1kHz 1.50% 10kHz 5.00% 100kHz
Insulation Resistance:	30 GOhms
Inductance:	4 nH

Packaging Specifications		
Packaging:	Tube	
Packaging Quantity:	21	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

Downloaded From Oneyac.com



© 2006 - 2019 KEMET

单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)