
KEMET Part Number: MMK15155K250B14L20ABULK

(F601BV155K250ALL0A)



MMK/F601, Film, Metallized Polyester, General Purpose, 1.5 uF, 10%, 250 VDC, 85°C, Lead Spacing = 15mm



General Information	
Series:	MMK/F601
Dielectric:	Metallized Polyester
Style:	Radial
Features:	DC Multipurpose Applicatiions
RoHS:	Yes
Lead:	Wire Leads
Notes:	Not For New Design, Please Check Possible Alternative Parts (AltPart)

Dimensions	
L	18mm MAX
Н	17.5mm MAX
Т	9.5mm MAX
S	15mm +/-0.4mm
LL	20mm NOM
F	0.8mm NOM

Specifications	
Capacitance:	1.5 uF
Capacitance Tolerance:	10%
Voltage AC:	160 VAC
Voltage DC:	250 VDC, 193.8 VDC (100C)
Temperature Range:	-55/+100C
Rated Temperature:	85°C
Insulation Resistance:	6.6667 GOhms
Max dV/dt:	12 V/us

Packaging Specifications		
Packaging:	Bulk, Bag	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

Downloaded From Oneyac.com



© 2006 - 2019 KEMET

单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)