


ALS37, Aluminum Electrolytic, 100,000 uF, -10/+30%, 40 VDC, -40/+85°C



General Information	
<b>Series:</b>	ALS37
<b>Dielectric:</b>	Aluminum Electrolytic
<b>Description:</b>	Screw Terminal, Aluminum Electrolytic
<b>RoHS:</b>	Yes
<b>Mounting:</b>	Stud
<b>AEC-Q200:</b>	No
<b>Notes:</b>	Add 0.015 in/ 0.4 mm to D and 0.045 in/ 1.1 mm to L for sleeving. Dimension LT Available On Request. MS (MxH) = M12x16

Dimensions	
<b>D</b>	50.8mm +/-0.787mm
<b>L</b>	142.875mm +/-1.575mm
<b>T</b>	5.512mm +/-0.787mm
<b>S</b>	22.225mm +/-0.483mm
<b>DT</b>	8.001mm +/-0.483mm
<b>TD</b>	10.008mm MIN
<b>V</b>	13.691mm NOM

Specifications	
<b>Capacitance:</b>	100,000 uF
<b>Capacitance Tolerance:</b>	-10/+30%
<b>Voltage DC:</b>	40 VDC, 50 VDC (Surge)
<b>Temperature Range:</b>	-40/+85°C
<b>Rated Temperature:</b>	85°C
<b>Life:</b>	18000 Hrs (Rated Voltage And Ripple Current At 85C), 36000 Hrs (Rated Voltage At 85C)
<b>Resistance:</b>	9 mOhms (120Hz 25C), 8 mOhms (20kHz 25C)
<b>Ripple Current:</b>	21.7 Amps (120Hz 85C), 23.1 Amps (20kHz 85C)
<b>Leakage Current:</b>	6000 uA (5min 20°C)

Packaging Specifications	
<b>Weight:</b>	425 g
<b>Packaging:</b>	Bulk, Box

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)