

KEMET Part Number: PHE450KT7150JR06L2 **Not for New Design**
(F450FQ155J400Z)

PHE450/F450, Film, Double Metallized Polypropylene, General Purpose, 1.5 uF, 5%, 400 VDC, 85°C, Lead Spacing = 27.5mm



General Information	
Series:	PHE450/F450
Dielectric:	Double Metallized Polypropylene
Style:	Radial
Features:	Pulse
RoHS:	Yes
Lead:	Wire Leads
AEC-Q200:	No
Miscellaneous:	The Rated Voltage Decreases 1.3%/C Between +85C And +105C. Rthha= 27 C/W (85C), 0.2 m/s

Dimensions	
L	31.5mm MAX
H	16mm MAX
T	27.5mm MAX
S	27.5mm +0.4/-0.4mm
LL	18.5mm +0.5mm
F	0.8mm +/-0.05mm
G	0.5mm NOM

Specifications	
Capacitance:	1.5 uF
Capacitance Tolerance:	5%
Voltage AC:	250 VAC
Voltage DC:	400 VDC (85C), 296 VDC (105C)
Temperature Range:	-55/+105°C
Rated Temperature:	85°C
Dissipation Factor:	0.03% 1kHz
Insulation Resistance:	20 GOhms
Max dV/dt:	500 V/us
Inductance:	6 nH

Packaging Specifications	
Packaging:	Pizza, Box
Packaging Quantity:	81

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)