
## KEMET Part Number: 10HV63R472K

(10HV63R472K)



## HV RAD-LDD Mil X7R HV 49467, Ceramic, 4700 pF, 10%, 1000 VDC, X7R, Lead Spacing = 9.53mm



Dimensions	
L	11.938mm MAX
Н	10.16mm MAX
Т	6.858mm MAX
S	9.525mm +/-0.762mm
LL	31.75mm MIN
F	0.635mm NOM

Packaging Specifications	
Packaging:	Bulk, Bag
Packaging Quantity:	1

General Information		
Series:	HV RAD-LDD Mil X7R HV 49467	
Style:	Radial	
RoHS:	No	
Prop 65:	WARNING: Cancer and reproductive harm - www.p65warnings.ca.gov.	
REACH:	SVHC (Pb – CAS 7439-92-1)	
Termination:	Lead (SnPb)	
Failure Rate:	N/A	

Specifications		
Capacitance:	4700 pF	
Capacitance Tolerance:	10%	
Voltage DC:	1000 VDC	
Dielectric Withstanding Voltage:	1500 VDC	
Temperature Range:	-55/+200C	
Temperature Coefficient:	X7R	
Dissipation Factor:	2.5%	
Insulation Resistance:	100 GOhms	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.





单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)