

KEMET Part Number: MMC12.7224J250B31BULK
(F160YR224J250A)

MMC/F160, Film, Metallized Polyester, General Purpose, 0.22 uF, 5%, 160 VAC, 250 VDC, 100°C, 5045, 6.5mm



Note: '()' correspond to the letters used in the product bulletin

| Dimensions | |
|------------|-----------------|
| Chip Size | 5045 |
| L | 12.7mm +/-0.2mm |
| W | 11.5mm +/-0.2mm |
| T | 6.5mm +/-0.2mm |
| F | 0.5mm NOM |

| Packaging Specifications | |
|--------------------------|-----------|
| Packaging: | Bulk, Bag |
| Packaging Quantity: | 1000 |

| General Information | |
|---------------------|-------------------------------------|
| Series: | MMC/F160 |
| Dielectric: | Metallized Polyester |
| Style: | SMD Chip |
| RoHS: | Yes |
| AEC-Q200: | No |
| Miscellaneous: | Not For New Design. Use Series F161 |
| Shelf Life: | 104 Weeks |

| Specifications | |
|------------------------|---------------------------------------|
| Capacitance: | 0.22 uF |
| Capacitance Tolerance: | 5% |
| Voltage AC: | 160 VAC |
| Voltage DC: | 250 VDC |
| Temperature Range: | -55/+100C |
| Rated Temperature: | 100°C |
| Dissipation Factor: | 0.80% 1kHz, 1.20% 10kHz, 3.00% 100kHz |
| Insulation Resistance: | 15 GOhms |
| Max dV/dt: | 20 V/us |

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)