
KEMET Part Number: MDK10105J250A58P7TUBE

(F687AA105J250T)



MDK/F68, Film, Metallized Polyester, Dual-In-Line, 1 uF, 5%, 160 VAC, 250 VDC, 85°C, 10mm



| General Information | |
|---------------------|----------------------|
| Series: | MDK/F68 |
| Dielectric: | Metallized Polyester |
| Style: | Dual-In-Line |
| RoHS: | Yes |
| Lead: | Wire Leads |
| AEC-Q200: | No |

| Dimensions | |
|------------|------------------|
| L | 23mm +/-0.2mm |
| L2 | 3.88mm MAX |
| W | 12.7mm +/-0.2mm |
| Н | 11mm +/-0.2mm |
| H1 | 14.2mm +1mm |
| S | 10mm +/-0.2mm |
| S1 | 2.54mm +/-0.2mm |
| S2 | 15.24mm +/-0.2mm |
| LL | 3.2mm +1mm |
| F | 0.5mm +/-0.05mm |
| E | 0.2mm MAX |
| G | 0.3mm MAX |
| Х | 0.35mm +/-0.05mm |

| Specifications | |
|------------------------|--|
| Capacitance: | 1 uF |
| Capacitance Tolerance: | 5% |
| Voltage AC: | 160 VAC |
| Voltage DC: | 250 VDC |
| Temperature Range: | -55/+125°C |
| Rated Temperature: | 85°C |
| Dissipation Factor: | 0.80% 1kHz 1.50% 10kHz 5.00% 100kHz |
| Insulation Resistance: | 10 GOhms |
| Inductance: | 4 nH |

| Packaging Specifications | | |
|--------------------------|------|--|
| Packaging: | Tube | |
| Packaging Quantity: | 21 | |

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information of otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

Generat



fc5df

单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)