

C4AE, Film, Metallized Polypropylene, DC Link, 4.5 uF, 5%, 450 VDC, 70°C, Lead Spacing = 27.5mm



Dimensions

L	31.5mm +0.5mm
H	20mm +0.2mm
T	11mm +0.3mm
S	27.5mm +/-0.4mm
LL	6mm -2mm
F	0.8mm NOM
G	0.5mm NOM

Packaging Specifications

Packaging:	Bulk, Box
-------------------	-----------

General Information

Series:	C4AE
Dielectric:	Metallized Polypropylene
Style:	Radial
RoHS:	Yes
Termination:	Tin
Lead:	Wire Leads
AEC-Q200:	No
Miscellaneous:	Thermal Resistance = 44 C/W

Specifications

Capacitance:	4.5 uF
Capacitance Tolerance:	5%
Voltage DC:	450 VDC
Temperature Range:	-40/+85°C
Rated Temperature:	70°C
Insulation Resistance:	6.67 MOhms
Max dV/dt:	14 V/us
Resistance:	14.2 mOhms (10kHz 70C)
Ripple Current:	4.5 Amps (10kHz 70C), 65 Amps (Peak)
Inductance:	25 nH

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)