

KEMET Part Number: PHE840MB5470MB04R035J
(F840BD473M275CL35J)

PHE840M/F840, Film, Metallized Polypropylene, Safety, 0.047 uF, 20%, 275 VAC (X2), 760 VDC, 105°C, Lead Spacing = 15mm



| General Information | |
|---------------------|---|
| Series: | PHE840M/F840 |
| Dielectric: | Metallized Polypropylene |
| Style: | Radial |
| Features: | EMI Safety |
| RoHS: | Yes |
| Lead: | Wire Leads |
| Qualifications: | ENEC, UL, cUL |
| Notes: | Not For New Design, Please Check Possible Alternative Parts (AltPart) |

| Dimensions | |
|------------|---------------|
| L | 18mm MAX |
| H | 10.5mm MAX |
| T | 5.5mm MAX |
| S | 15mm +/-0.4mm |
| LL | 3.5mm NOM |
| F | 0.8mm NOM |

| Specifications | |
|------------------------|---------------------------------------|
| Capacitance: | 0.047 uF |
| Capacitance Tolerance: | 20% |
| Voltage AC: | 275 VAC (X2) |
| Voltage DC: | 760 VDC |
| Temperature Range: | -55/+105C |
| Rated Temperature: | 105°C |
| Dissipation Factor: | 0.10% 1kHz, 0.20% 10kHz, 0.60% 100kHz |
| Insulation Resistance: | 30 GOhms |
| Max dV/dt: | 100 V/us |
| Safety Class: | X2 |

| Packaging Specifications | |
|--------------------------|-----------|
| Packaging: | Bulk, Bag |
| Packaging Quantity: | 1000 |

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)