


KEMET Part Number: HT05CN331JN
(HT05CN331J)

HTHP LDD Indust COG HT200C, Ceramic, 330 pF, 5%, 100 VDC, COG, Commercial, High Temperature, Lead Spacing = 2.54mm



Dimensions

| Dimension | Value |
|-----------|------------------|
| L | 5.08mm MAX |
| H | 5.08mm MAX |
| T | 2.54mm MAX |
| S | 2.54mm +/-0.76mm |
| LL | 31.75mm MIN |
| F | 0.635mm NOM |

Packaging Specifications

| | |
|----------------------------|-----------|
| Packaging: | Bulk, Bag |
| Packaging Quantity: | 1 |

General Information

| | |
|----------------------|------------------------------|
| Series: | HTHP LDD Indust COG HT200C |
| Style: | Radial |
| Description: | Commercial, High Temperature |
| Features: | Commercial |
| RoHS: | Yes |
| Termination: | Nickel |
| Failure Rate: | N/A |
| AEC-Q200: | No |

Specifications

| | |
|---|------------|
| Capacitance: | 330 pF |
| Capacitance Tolerance: | 5% |
| Voltage DC: | 100 VDC |
| Dielectric Withstanding Voltage: | 250 VDC |
| Temperature Range: | -55/+200°C |
| Temperature Coefficient: | COG |
| Dissipation Factor: | 0.15% |
| Insulation Resistance: | 100 GOhms |

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)