
KEMET Part Number: HT55BB392JN

(HT55BB392J, HT55BW392JN)



HTHP LDD Indust X7R HT200C, Ceramic, 3900 pF, 5%, 50 VDC, X7R, Commercial, High Temperature, Lead Spacing = 5.08mm



Dimensions		
L	5.08mm MAX	
Н	5.08mm MAX	
Т	2.54mm MAX	
S	5.08mm +/-0.76mm	
LL	31.75mm MIN	
F	0.635mm NOM	
G	1.65mm MAX	

Packaging Specifications		
Packaging:	Bulk, Bag	
Packaging Quantity:	1	

General Information		
Series:	HTHP LDD Indust X7R HT200C	
Style:	Radial	
Description:	Commercial, High Temperature	
Features:	Commercial	
RoHS:	Yes	
Termination:	Nickel	
Failure Rate:	N/A	
AEC-Q200:	No	

Specifications		
Capacitance:	3900 pF	
Capacitance Tolerance:	5%	
Voltage DC:	50 VDC	
Dielectric Withstanding Voltage:	125 VDC	
Temperature Range:	-55/+200°C	
Temperature Coefficient:	X7R	
Dissipation Factor:	2.50%	
Insulation Resistance:	100 GOhms	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.





单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)