## KEMET Part Number: MDC15334J400B55P4TUBE

(F154AB334J400T)



**General Information** 

**Specifications** 

MDC

Yes

L Leads

0.33 uF

200 VAC

400 VDC

-55/+125C

0.8% 1kHz, 1.5% 10kHz, 5%

85°C

100kHz 30 GOhms

4 nH

5%

Metallized Polyester

Dual-In-Line

Series:

Style:

RoHS:

Lead:

Capacitance:

Voltage AC:

Voltage DC:

Inductance:

**Capacitance Tolerance:** 

**Temperature Range:** 


**Rated Temperature:** 

**Dissipation Factor:** 

**Insulation Resistance:** 

**Dielectric:** 

## MDC, Film, Metallized Polyester, 0.33 uF, 5%, 200 VAC, 400 VDC, 85°C



Dimensions		
L	12.2mm +/-0.2mm	
W	16.5mm +/-0.2mm	
Т	6.05mm +/-0.2mm	
F	0.5mm +/-0.05mm	

Packaging Specifications	
Packaging:	Bulk, Tube
Packaging Quantity:	39

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and	
we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the	
requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us	
with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.	





单击下面可查看定价,库存,交付和生命周期等信息

>>KEMET(基美)