

KEMET Part Number: MMC16.5565K50C31TV44
(F160ZS565K050Y)

MMC/F160, Film, Metallized Polyester, General Purpose, 5.6 uF, 10%, 30 VAC, 50 VDC, 100°C, 6560, 7mm



Note: '()' correspond to the letters used in the product bulletin

Dimensions	
Chip Size	6560
L	16.5mm +/-0.2mm
W	15mm +/-0.2mm
T	7mm +/-0.2mm
F	0.5mm NOM

Packaging Specifications	
Packaging:	T&R, Vertical Orientation
Packaging Quantity:	200

General Information	
Series:	MMC/F160
Dielectric:	Metallized Polyester
Style:	SMD Chip
RoHS:	Yes
Miscellaneous:	Not For New Design. Use F161ZS565K050Y (Series F161)

Specifications	
Capacitance:	5.6 uF
Capacitance Tolerance:	10%
Voltage AC:	30 VAC
Voltage DC:	50 VDC
Temperature Range:	-55/+100C
Rated Temperature:	100°C
Dissipation Factor:	0.80% 1kHz, 1.50% 10kHz
Insulation Resistance:	892.9 MOhms
Max dV/dt:	5 V/us

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)