

**KEMET Part Number: MMC7.3274J50K35TR12**  
(F160SP274J050V)

MMC/F160, Film, Metallized Polyester, General Purpose, 0.27 uF, 5%, 30 VAC, 50 VDC, 100°C, 2824, 3.5mm



Note: '()' correspond to the letters used in the product bulletin

| Dimensions |                |
|------------|----------------|
| Chip Size  | 2824           |
| L          | 7.3mm +/-0.2mm |
| W          | 6mm +/-0.2mm   |
| T          | 3.5mm +/-0.2mm |
| F          | 0.5mm NOM      |

| Packaging Specifications |      |
|--------------------------|------|
| Packaging:               | T&R  |
| Packaging Quantity:      | 2300 |

| General Information |                                     |
|---------------------|-------------------------------------|
| Series:             | MMC/F160                            |
| Dielectric:         | Metallized Polyester                |
| Style:              | SMD Chip                            |
| RoHS:               | Yes                                 |
| Miscellaneous:      | Not For New Design. Use Series F161 |

| Specifications         |                                  |
|------------------------|----------------------------------|
| Capacitance:           | 0.27 uF                          |
| Capacitance Tolerance: | 5%                               |
| Voltage AC:            | 30 VAC                           |
| Voltage DC:            | 50 VDC                           |
| Temperature Range:     | -55/+100C                        |
| Rated Temperature:     | 100°C                            |
| Dissipation Factor:    | 0.8% 1kHz, 1.2% 10kHz, 3% 100kHz |
| Insulation Resistance: | 15 GOhms                         |
| Max dV/dt:             | 25 V/us                          |

单击下面可查看定价，库存，交付和生命周期等信息

[>>KEMET\(基美\)](#)