


RECOMMEND PCB LAYOUT
TOLERANCE $\pm 0.05\text{mm}$

NOTES:

1. MATERIAL:
 - 1.1 HOUSING: THERMOPLASTIC, HIGH TEMP., UL94V-0. COLOR: NATURE
 - 1.2 CONTACT: COPPER ALLOY.
2. FINISH:
 - 2.1 CONTACT: 50~100u" NICKEL UNDERPLATING OVERALL.
- P: 8u" MIN GOLD ON CONTACT AND GOLD FLASH ON SOLDER
3. REFLOW SOLDER CAPABLE TO 260°C PER ACES SPEC.
4. SPEC. PLS REFER TO PS-51039-XXXXX-XXX
5. PACKAGE PLS REFER TO 51039-XXXXX-XX-TRP
6. PART NUMBER



51039-XXX X X-XXX


XXX	Material&Color
001	LCP&NATURE

PLATING

P: 8u" MIN GOLD ON CONTACT (LEAD FREE)

PACKING

4: TAPE REEL & WITH MYLAR



CKT	DIM A	DIM B	DIM C	DIM D	DIM E	DIM F
60	29.80	23.20	28.20	26.80	28.15	25.8
100	45.80	39.20	44.20	42.80	44.15	41.8

一般公差 TOLERANCES X ± 0.50 .XX ± 0.15 X ± 0.25 .XXX ± 0.10 ANGLES $\pm 2^\circ$		宏致電子股份有限公司 Aces Electronics Co., Ltd.	
檢驗尺寸標示 SYMBOLS \odot \ominus INDICATE CLASSIFICATION DIMENSION \ominus MARK IS CRITICAL DIM. \odot MARK IS MAJOR DIM.	品名 (TITLE) 0.8 mm PITCH BTB RECT CONN. SMT D/R S/T TYPE	製圖 (DR) 15/01/14 JUGG	審核 (CHKD) BRAVE
圖號 (DWG NO.) 51039-XXXXX-XXX		核准 (APPD) FRANK	
表面處理 (FINISH)	比例 (SCALE) 2:1	單位 (UNITS) mm	張數 (SHEET) 1 OF 1
			SIZE A4
		REV A	

单击下面可查看定价，库存，交付和生命周期等信息

[>>ACES \(宏致\)](#)