

TO:	文件编号	HXA-L06-24(05)
	发行日期	2013年12月24日

承认规格书

种类: 功率电感

系列号: FWP565048N-Series-HD

客户料号: _____

客户承认栏	
承认日期	年 月 日

(贵司承认后请签署一份返回华信安电子, 谢谢!)

厦门华信安电子科技有限公司技术质量部

承认	确认	作成
龙梅	梁峰	王亮

TEL: 0592-6301603 FAX: 0592-5205265

Http: www.xmisnd.com



SMD Power Inductor

FWP565048N-Series-HD

ECN HISTORY LIST

REV	DATE	DESCRIPTION	APPROVED	CHECKED	DRAWN
1.0	13/12/24	新发行	龙梅	梁峰	王亮

备注	
----	--



SMD Power Inductor

FWP565048N-Series-HD

1. Features


1. Small and Low profile inductor
2. It corresponds to High current.
3. Simple and Shield structure.
4. Available tape and reel for auto insertion.
5. 100% Lead(Pb)-Free and RoHS compliant.




2. Applications

-For small DC/DC converter(cellular phone,LCD/LED/OLED display, HDD, DSC etc)

3. Dimensions



Recommend Land pattern



	A(mm)	B(mm)	C(mm)	D(mm)	E(mm)	F(mm)
FWP565048N	5.60±0.3	5.00±0.3	4.50±0.3	2.0±0.3	3.8±0.3	3.1±0.3

L(mm)	G(mm)	H(mm)
6.0	1.7	5.5

4. Part Numbering



- A: Series
- B: Dimension
- C: Type
- D: Inductance
- E: Inductance Tolerance
- F: Holder

A*B*C

2R2=2.20uh 100=10uh,101=100uh,102=1000uh
K=±10%,M=±20%.

印字: 黑色, 单向印字

marking direction cannot decide polarity. Color: Black, unidirectional.

No magnetic shielding

5. Specification


Part Number	Inductance L0 (uH) @ 0 A	Tolerance	Frequency (Hz/1V)	Rated current		DCR (mΩ) @25°C ± 20%.
				Tempetature current I rms (A)	Saturation current I sat (A)	
FWP565048N-1R0M-HD	1.00	± 20%	7.96M	7.00	6.00	10.0
FWP565048N-1R5M-HD	1.50	± 20%	7.96M	6.00	5.00	13.0
FWP565048N-2R2M-HD	2.20	± 20%	7.96M	4.50	4.30	16.0
FWP565048N-3R3M-HD	3.30	± 20%	7.96M	4.20	3.60	21.0
FWP565048N-4R7M-HD	4.70	±20%	7.96M	3.80	3.20	26.0
FWP565048N-6R8M-HD	6.80	±20%	7.96M	3.00	2.60	39.0
FWP565048N-100K-HD	10.0	±10%	2.52M	2.20	2.00	60.5
FWP565048N-120K-HD	12.0	±10%	2.52M	2.00	1.80	72.0
FWP565048N-150K-HD	15.0	±10%	2.52M	1.80	1.60	86.0
FWP565048N-220K-HD	22.0	±10%	2.52M	1.50	1.35	143
FWP565048N-330K-HD	33.0	±10%	2.52M	1.30	1.10	198
FWP565048N-470K-HD	47.0	±10%	2.52M	1.10	0.90	252
FWP565048N-680K-HD	68.0	±10%	2.52M	1.00	0.80	360
FWP565048N-101K-HD	100	±10%	1K	0.80	0.70	505
FWP565048N-121K-HD	120	±10%	1K	0.70	0.60	615
FWP565048N-151K-HD	150	±10%	1K	0.60	0.55	750
FWP565048N-221K-HD	220	±10%	1K	0.55	0.43	1000

Note:

1. All test data referenced to 25°C ambient.
2. Testing Instrument : L/Q: HP4284A,CH11025,CH3302,CH1320 ,CH1320S LCR METER / Rdc:CH16502,Agilent33420A MICRO OHMMETER.
3. Heat Rated Current (I rms) will cause the coil temperature rise approximately Δ t of 40°C (keep 1min.).
4. Saturation Current (I sat) will cause L0 to drop 30% typical. (keep quickly).
5. The part temperature (ambient + temp rise) should not exceed 125°C under worst case operating conditions.Circuit design,component,PCB trace size and thickness,airflow and other cooling provisions all affect the part temperature. Part temperature should be verified in the end application.
6. Special inquiries besides the above common used types can be met on your requirement.



6. Material List



NO	Items	Materials
a	Core	Ferrite DR Core.
b	Wire	Enamelled Copper wire.
c	Terminal	Sn

7. Reliability and Test Condition

Item	Performance	Test Condition
Operating temperature	-40~+125℃	
Storage temperature and Humidity range	-10~+40℃, 50~60%RH (Product without taping)	
Electrical Performance Test		
Inductance	Refer to standard electrical characteristics list.	HP4284A, CH11025, CH3302, CH1320, CH1320S LCR Meter.
DCR		CH16502, Agilent33420A Micro-Ohm Meter.
Saturation Current (Isat)	△L30% typical.	Saturation DC Current (Isat) will cause L0 to drop △L(%) (keep quickly).
Heat Rated Current (Irms)	Approximately △T≦40℃	Heat Rated Current (Irms) will cause the coil temperature rise △T(℃) without core loss. 1. Applied the allowed DC current (keep 1 min.). 2. Temperature measured by digital surface thermometer
Reliability Test		
High Temperature Exposure Test	Electric specifications should be satisfied	Temperature: 125±2℃ . Duration: 1000±12hrs. Measured at room temperature after placing for 2 to 3hrs. (MIL-PRF-27)
Low Temperature Life Test		Temperature: -40±2℃ . Duration: 500±12hrs. Measured at room temperature after placing for 2 to 3hrs.
Biased Humidity Test		Humidity: 85±3%RH. Temperature: 85±2℃ . Duration: 1000±12hrs. Measured at room temperature after placing for 2 to 3hrs (AEC-Q200-REV C)
Thermal shock test		Condition for 1 cycle Step1: -40+0 / -2℃ 15±1 min. Step2: Room temperature within ≦0.2 min. Step3: +125+2 / -0℃ 15±1min. Number of cycles: 300 Measured at room temperature after placing for 2 to 3 hrs. (AEC-Q200-REV C)
Vibration test		Frequency: 10-2000-10Hz for 20 min. Amplitude: Parts mounted within 2" from any secure point. Directions and times: X, Y, Z directions for 20 min. This cycle shall be performed 12 times in each of three mutually perpendicular directions (Total 12hours). (MIL-STD-202 Method 204 D Test condition B)
Reflow test		Pre-heat: 150±5℃ Duration: 5 minutes Temperature: 260±5℃, 5-10 seconds (IPC/JEDEC J-STD-020C)
Solder test		Terminals should be covered by over 95% solder on visual inspection After dip into flux, dip into solder 235±5℃, 4±1seconds Flux, solder for lead free (ANSI /J-STD-002C Method B)

8. Soldering and Mounting

(1) Soldering

Mildly activated rosin fluxes are preferred. The minimum amount of solder can lead to damage from the stresses caused by the difference in coefficients of expansion between solder, chip and substrate. TAIPAQ terminations are suitable for re-flow soldering systems. If hand soldering cannot be avoided, the preferred technique is the utilization of hot air soldering tools.

(2) Solder re-flow:

Recommended temperature profiles for re-flow soldering in Figure 1.

(3) Soldering Iron:

Products attachment with a soldering iron is discouraged due to the inherent process control limitations. In the event that a soldering iron must be employed the following precautions are recommended.

- Preheat circuit and products to 150°C
- Never contact the ceramic with the iron tip
- Use a 20 watt soldering iron with tip diameter of 1.0mm
- Limit soldering time to 4-5sec.
- 355°C tip temperature (max)
- 1.0mm tip diameter (max)




Fig.1





Fig.2


9. Packaging Information

(1) Reel Dimension



Type	A(mm)	B(mm)	C(mm)	D(mm)
13"x12mm	13.5±1.0	100±2.0	13.5±0.5	330±3.0

(2) Tape Dimension




Series	Size	Bo(mm)	Ao(mm)	Ko(mm)	P(mm)	w(mm)	t(mm)	Emm)	F(mm)	D(mm)	Po(mm)	P2(mm)
FWP	565048	6.1±0.1	5.4±0.1	5.0±0.1	8.0±0.1	12±0.3	0.35±0.1	1.75±0.1	5.50±0.1	1.5±0.1	4.0±0.1	2.00±0.1

(3) Packaging Quantity

FWP	565048
Reel	1500
Inner box	3000
Carton	12000

(4) Tearing Off Force



The force for tearing off cover tape is 10 to 130 grams in the arrow direction under the following conditions(referenced ANSI/EIA-481-C-2003 of 4.11 stadnard).

Room Temp.(°C)	Room Humidity(%)	Room atm(hPa)	Tearing Speedmm/min
5~35	45~85	860~1060	300

Application Notice

Storage Conditions

To maintain the solderability of terminal electrodes:


1. TAIPAQ products meet IPC/JEDEC J-STD-020D standard-MSL, level 1.
2. Temperature and humidity conditions: Less than 40 °C and 60% RH.
3. Recommended products should be used within 12 months form the time of delivery.
4. The packaging material should be kept where no chlorine or sulfur exists in the air.



Transportation

1. Products should be handled with care to avoid damage or contamination from perspiration and skin oils.
2. The use of tweezers or vacuum pick up is strongly recommended for individual components.
3. Bulk handling should ensure that abrasion and mechanical shock are minimized.



10. Typical Performance Curves





单击下面可查看定价，库存，交付和生命周期等信息

[>>ISND\(华信安\)](#)