

The history of revision change for the specification

| Document      | REV. | Modified date | Description   |
|---------------|------|---------------|---|
| CYNVC-19X-030 | A0   | 2019.10.17    | New approval  |
| CYNVC-19X-030 | A1   | 2019.11.12    | 1. Oct. -> Nov<br>2. Remove R47 spec and curve<br>3. Add 1R0, 1R5, 3R3 spec and curve<br>4. Update 220 spec<br>Idc(Typ./Max.): 2.5/2.3 -> 2.8/2.5 |
| CYNVC-19X-030 | A2   | 2020.1.13     | 1. Nov., 2019 -> Jan., 2020<br>2. Year Code: 2019 = 9 -> 2020 = 0<br>3. Remove frequency: (1MHz) from Features                                    |
| CYNVC-19X-030 | A3   | 2020.3.31     | 1. Jan. -> Mar.<br>2. Add 2R2 spec and curve  |
| CYNVC-19X-030 | A4   | 2020.4.7      | 1. Mar., -> Apr.,<br>2. Add R47 spec and curve  |
| CYNVC-19X-030 | A5   | 2020.4.10     | 1. Add "AEC-Q200" logo<br>2. Add notice "AEC-Q200 qualified" in Features<br>3. Remove Notice "Preliminary specification"                          |

### Power Choke Coil VCMT063T MN5TM type

AEC-Q200

#### ■ Features

High performance (Isat) realized by metal dust core.

Low profile : Thickness max. 3.0mm

Low loss realized with low DCR

Capable of corresponding high frequency


Compliance with RoHS and Halogen Free

AEC-Q200 qualified

#### ■ Application

Automotive applications


#### ■ Outline Dimensions



| Code | Dimensions (mm) |
|------|-----------------|
| L    | $6.95 \pm 0.35$ |
| W    | $6.6 \pm 0.2$   |
| T    | $2.8 \pm 0.2$   |
| A1   | $1.27 \pm 0.30$ |
| A'   | $2.0 \pm 0.1$   |
| B    | $3.18 \pm 0.30$ |
| B1   | $4.3 \pm 0.3$   |
| B'   | $3.6 \pm 0.2$   |
| H    | $0 \sim +0.15$  |

#### ■ Recommend Land Pattern Dimensions

The customer shall determine the land dimensions shown below after confirming and safety.



|   |       |
|---|-------|
| A | 3.429 |
| B | 3.429 |
| C | 8.255 |

Unit : mm

### ■ Marking and Date Code

The point on the top surface represents winding direction of choke.

#### (1) Marking

The inductor is marked with a 3-digit code

Example --  $4.7\mu\text{H}$  → 4R7

#### (2) Date Code

X    XX

(1)    (2)

XXX

(3)

Where (1) Year Code

Ex : 2020 = 0


(2) Weekly Code

Serial number : 01 ~ 53

(3) Taping No.

Serial number : 001 ~ ZZZ

Upside of Chip



Coil clockwise around

### ■ Specifications

| Part Number       | L0 ◇<br>Inductance<br>( μH )<br>@ (0A) | R <sub>dc</sub> ( mΩ ) ◇ |         | Heat Rating Current<br>DC Amps. I <sub>dc</sub> ( A ) |         | Saturation Current<br>DC Amps. I <sub>sat</sub> ( A ) |         | Rated Voltage<br>( V ) |
|-------------------|--|--------------------------|---------|---|---------|---|---------|------------------------|
|                   |  | Typical                  | Maximum | Typical   | Maximum | Typical   | Maximum | Maximum                |
| VCMT063T-R47MN5TM | 0.47                                   | 3.85                     | 4.62    | 17.0  | 15.3    | 16.3  | 14.0    | 75                     |
| VCMT063T-1R0MN5TM | 1.0                                    | 6.5                      | 7.8     | 13.0  | 11.7    | 13.0  | 11.1    | 75                     |
| VCMT063T-1R5MN5TM | 1.5                                    | 10.9                     | 12.5    | 10.6  | 9.5     | 11.6  | 9.9     | 75                     |
| VCMT063T-2R2MN5TM | 2.2                                    | 15.0                     | 16.5    | 9.0   | 8.1     | 8.0   | 6.9     | 75                     |
| VCMT063T-3R3MN5TM | 3.3                                    | 22.5                     | 26.0    | 7.5   | 6.8     | 8.3   | 7.1     | 75                     |
| VCMT063T-4R7MN5TM | 4.7                                    | 31.5                     | 33.4    | 6.0   | 5.4     | 6.0   | 5.1     | 75                     |
| VCMT063T-6R8MN5TM | 6.8                                    | 41.5                     | 46.8    | 5.5   | 5.0     | 4.5   | 3.9     | 75                     |
| VCMT063T-100MN5TM | 10.0                                   | 61.0                     | 70.5    | 4.0   | 3.6     | 3.5   | 3.0     | 75                     |
| VCMT063T-150MN5TM | 15.0                                   | 96.0                     | 110.0   | 3.2   | 2.9     | 2.8   | 2.4     | 75                     |
| VCMT063T-220MN5TM | 22.0                                   | 163.0                    | 174.0   | 2.8   | 2.5     | 2.4   | 2.1     | 75                     |

◇ : Significant Characteristic

\* : If you require another part number please contact with us.

\*\* : Inductance Tolerance  $\pm 20\%$

Note 1. : All test data is referenced to 25°C ambient.

Note 2. : Test Condition: 100KHz, 1.0Vrms

Note 3. : I<sub>dc</sub> : DC current (A) that will cause an approximate  $\Delta T$  of 40°C

Note 4. : I<sub>sat</sub> : DC current (A) that will cause L0 to drop approximately 20%

Note 5. : Operating Temperature Range -55°C to +155°C

Note 6. : The part temperature (ambient + temp rise) should not exceed 155°C under the worst case operating conditions. Circuit design, component placement, PCB trace size and thickness, airflow and other cooling provision all affect the part temperature. Part temperature should be verified in the end application.

Note 7. : The rated current as listed is either the saturation current or the heating current depending on which value is lower.









Note 8. : Cleaning Process Note



(a) If this power choke is dipped in the cleaning agent, such as toluene, xylene, ketone, and ether system, there is a possibility that the performance decreases greatly

(b) The high power ultrasonic washing may damage the choke body.

(c) Please contact us if you need the cleaning via the above agents or ultrasonic washing.


### Current Characteristic





**■ Packaging**


(1) Tape packaging dimensions




| Dimensions Code (mm) |           |           |             | UNITS/REEL |
|----------------------|-----------|-----------|-------------|------------|
| A0                   | B0        | K0        | t           |            |
| 7.10 ± 0.15          | 7.5 ± 0.1 | 3.6 ± 0.1 | 0.35 ± 0.05 | 2,000      |

(2) Tape Direction

The direction shall be seen from the top cover tape side.




(3) Reel dimensions



(4) Peel force of top cover tape

The peel speed shall be about 300 mm/minute


The peel force of top cover tape shall be between 0.1 to 1.3N





■ Reflow Profile

Power Choke Coil Type



(1) Reflow Soldering Method :

|                               |                |                       |
|-------------------------------|----------------|-----------------------|
| Reflow Soldering              | Tp:255~260°C   | Max.30 seconds ( tp ) |
|                               | 217°C          | 60~150 seconds        |
| Pre-Heat                      | 150 ~ 200°C    | 60~120 seconds        |
| Time 25°C to peak temperature | 8 minutes max. |                       |

(2) Soldering iron Method : 350 ± 5°C max.3 seconds

单击下面可查看定价，库存，交付和生命周期等信息

[>>CYNTEC\(乾坤科技\)](#)