

REVISIONS							
REV	ECO	DESCRIPTION	DATE	BY	APPR		
B1	-	RELEASED DRAWING	JULY-03-2014	BEN	TOMMY		







NOTES: (UNLESS OTHERWISE SPECIFIED)

1. MATERIAL:

SHELL: ZINC ALLOY, NICKEL PLATED. INSERT: THERMOPLASTIC, UL94 V-0. END CAP: THERMOPLASTIC, UL94 V-0. COUPLING NUT: AL ALLOY, NICKEL PLATED.

WAVE WASHER: STAINLESS STEEL.

O-RING: NBR.

WIRE SEAL: SILICONE RUBBER.

PLASTIC BUSHING: THERMOPLASTIC, UL94 V-0.

2. SPECIFICATIONS:

2.1 RATED CURRENT: 23A (MAX). 2.2 RATED VOLTAGE: 350V (AC/DC).

2.3 OPERATING TEMPERATURE: -40°C ~+105°C. 2.4 DIELECTRIC WITHSTANDING VOLTAGE: LESS THAN 2 MILLIAMPS CURRENT LEAKAGE@2000 VOLTS AC. 2.5 INSULATION RESISTANCE: 5000 MEGOHMS MIN.

2.6 IP--CLASS: IP67.

2.7 MATING CYCLES DURABILITY: 500 CYCLES MIN.

2.8 ROHS COMPLIANT.

- 3. SUITABLE CONTACTS: 2.5mm CONTACTS.
- 4. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.
- 5. CONTACT SIZE AND REAR SEAL WIRE RANGE:

CONTACT SIZE	MIN. INSUL O.D.	MAX. INSUL O.D.	WIRE RANGE
2.5mm Ø3.3mm		Ø4.3mm	14-12AWG

PART NUMBER
RT06144SNHEC
RT06144SWHEC
RT06144SXHEC
RT06144SYHEC
RT06144SZHEC

	SEE PART N	JMBER CHART						
QUANTITY	Y PART NUMBER		DESCRIPTION		SCRIPTION	ITEM		
	MATERIALS LIST							
UNLESS OTHERWISE SPECIFIED 1) All dimensions are in metric(mm).		SIGNATURE	s	DATE	Amphenol			
2) Tolerances are	as follows:	DRAWN: BEN		JULY-03-2014	Amphenor			
2 PL DEC ±0.30 2 PL DEC ±0.15 3 PL DEC ±0.08							e Systems - www.amphenol-sine	com.
3) Note reference = \(\int X \) MATERIAL SPECIFICATIONS:		ENGINEER:			44724 Morley Drive Clinton Township, MI 48036			
		APPROVAL:				0		
		CUSTOMER:	'				ECO-MATE,PLUG,	
		THIS DRAWING IS SUPPLIED FO				SIZE	14,4POS,SOCKET,END CAP.	
PROCESS SPECIFICATIONS: SPECIFICATIONS AND PER SHOWN HEREON ARE THE THE AMPHENOL CORPOR. OF REPRODUCTION ARE IN DIMENSIONS ARE SHIRLD.		RFORM E PRO ATION IMPLIE	MANCE DATA PERTY OF N. NO RIGHTS ED. ALL	B	C-	RT06144S*HEC	B1	
NEXT ASS'Y:		MANUFACTURING VARIATIONS.		SCALE: N	ONE	SHEET 1 ОР	1	

Downloaded From Oneyac.com

RT06144S*HEC

ECO-MATE, PLUG, SIZE 14,4POS, SOCKET, END CAP

REV: B1 SH:

ecomate® RM/RSSM/Aquarius™ - Contact Size 12 Options

Machined, Crimp Contacts					
Part	Number	AWG	Wire Range	Diadia a	
Male	Female	AWG	(mm²)	Plating	
N/A					

Tooling, Machined					
Part Number	Description				
N/A	N/A				

Plating Options					
Symbol	Symbol Plating				
N/A	N/A				

Stamped & Formed, Crimp Contacts					
Part N	AWG	Wire Range	Plating		
Male	Female	AWG	(mm²)	ridiliig	
SP12A1T	SS12A1T	14-12	2.5-3.5	Tin	

Tooling, Stamped & Formed				
Part Number Description				
QXRT12S Contact Extraction Tool, 2.5mm Contact				
MFX-3962 Hand Tool, Stamped & Formed Contact, 2.5mm Contact				

Standard Quantity Order Options			
Machined	Stamped & Formed		
N/A	Reel, 1000 Pieces		

Amphenol Sine Systems 44724 Morley Drive Clinton Township, MI 48036 USA www.amphenol-sine.com 04/2021

单击下面可查看定价,库存,交付和生命周期等信息

>>Amphenol(安费诺)