



RECOMMENDED PCB LAYOUT  
GENERAL TOLERANCE ±0.05

- NOTES:
- MATERIAL:
    - HOUSING: HALOGEN FREE PLASTICS, UL94V-0; COLOR:NATURE.
    - CONTACT: COPPER ALLOY
  - FINISH:
    - CONTACT: GOLD FLASH OVERALL. 50u" MIN. NICKEL UNDERPLATING OVERALL.
  - REFLOW SOLDER CAPABLE TO 260° C PER ACES SPEC.
  - SPEC. PLS. REFER TO PS-50168-xxxxx-xxx
  - PACKAGE PLS. REFER TO 50169-XXXXX-TRP

6. PART NUMBER

50169-XXX X X-XXX

NO OF CKT: XXX  
PACKING: 0:TAPE&REEL  
1:TUBE

PLATING: 1: G/F OVERALL(LEAD FREE)

Material&Color: HF&Nature

△ 4:Tape & Reel with Mylar

CKT	DIM A	DIM B	DIM C	mylar
14	3.00	4.50	6.5	
50	12.00	13.50	15.5	W6T12-50169

一般公差 <b>TOLERANCES</b> X ±0.5 XX ±0.15 X ±0.25 .XXX ±0.1 ANGLES ±2°		宏致電子股份有限公司 <b>Aces Electronic Co.,Ltd.</b>	
檢驗尺寸標示 <b>SYMBOLS</b> (C) (M) INDICATE CLASSIFICATION DIMENSION (C) MARK IS CRITICAL DIM. (M) MARK IS MAJOR DIM.		品名 (TITLE) 0.5mm PITCH BTB RCPT CONN SMT D/R S/T MATED H=2.0mm 圖號 (DWG.NO) 50169-XXXXX-XXX	
表面處理 (FINISH)		比例 (SCALE) 單位 (UNITS) 8:1 mm	
檢驗 (DR) 09/03/19 製圖 (CHKD) SAM 核准 (APPD) JASON		圖號 (SHEET) 1 OF 1 尺寸 (SIZE) A4 版次 (REV) A	

单击下面可查看定价，库存，交付和生命周期等信息

[>>ACES\(宏致\)](#)