



- NOTES:
- MATERIAL:
 - HOUSING: HALOGEN FREE THERMOPLASTIC, HIGH TEMP., UL94V-0; COLOR:NATURAL OR BLACK
 - CONTACT: COPPER ALLOY
 - FITTING NAIL: COPPER ALLOY
 - ACTUATOR: HALOGEN FREE THERMOPLASTIC, HIGH TEMP., UL94V-0; COLOR:BLACK.
 - FINISH:
 - CONTACT:
 - 50~100u" NICKEL UNDERPLATING OVERALL.
 - 1: GOLD FLASH PLATING.
 - N: 100~150u" TIN PLATING.
 - T: 10u" GOLD ON CONTACT AREA
 - 3: 1u" GOLD ON CONTACT AREA AND SOLDER AREA
 - FITTING NAIL:
 - 50~100u" NICKEL UNDERPLATING OVERALL.
 - 100~150u" TIN PLATING.
 - REFLOW SOLDER CAPABLE TO 260°C PER ACES SPEC.
 - SPEC. PLS. REFER TO PS-50671-XXXX
 - PACKAGE PLS. REFER TO 91509-XXXX-TRP
 - PART NUMBER

50671-XXX X-XXX	XXX	Housing Color	Actuator Color	Halogen Free	TAPE & REEL PACKING
NO OF CKT	(0)1	Black	Black	HF	91509-XXXX
	(0)2	Black	Black	HF	91509-XXXX

PLATING
 1: GOLD FLASH
 2: TAPE & REEL
 N: MATT TIN
 1:TUBE
 4: TAPE & REEL WITH MYLAR
 5: TUBE WITH MYLAR
 3: 1u" GOLD ON CONTACT AREA
 1u" GOLD ON SOLDER AREA

CKT	DIM A	DIM B	DIM C	DIM D	CKT	DIM A	DIM B	DIM C	DIM D
4	6.20	1.50	2.56	3.0	33	20.70	16.00	17.06	15.0
5	6.70	2.00	3.06		34	21.20	16.50	17.56	
6	7.20	2.50	3.56		35	21.70	17.00	18.06	
7	7.70	3.00	4.06		36	22.20	17.50	18.56	
8	8.20	3.50	4.56		37	22.70	18.00	19.06	
9	8.70	4.00	5.06		38	23.20	18.50	19.56	
10	9.20	4.50	5.56		39	23.70	19.00	20.06	
11	9.70	5.00	6.06		40	24.20	19.50	20.56	
12	10.20	5.50	6.56		41	24.70	20.00	21.06	
13	10.70	6.00	7.06		42	25.20	20.50	21.56	
14	11.20	6.50	7.56		43	25.70	21.00	22.06	
15	11.70	7.00	8.06		44	26.20	21.50	22.56	
16	12.20	7.50	8.56	45	26.70	22.00	23.06		
17	12.70	8.00	9.06	46	27.20	22.50	23.56		
18	13.20	8.50	9.56	47	27.70	23.00	24.06		
19	13.70	9.00	10.06	48	28.20	23.50	24.56		
20	14.20	9.50	10.56	49	28.70	24.00	25.06		
21	14.70	10.00	11.06	50	29.20	24.50	25.56		
22	15.20	10.50	11.56	51	29.70	25.00	26.06		
23	15.70	11.00	12.06	52	30.20	25.50	26.56		
24	16.20	11.50	12.56	53	30.70	26.00	27.06		
25	16.70	12.00	13.06	54	31.20	26.50	27.56		
26	17.20	12.50	13.56	55	31.70	27.00	28.06		
27	17.70	13.00	14.06	56	32.20	27.50	28.56		
28	18.20	13.50	14.56	57	32.70	28.00	29.06		
29	18.70	14.00	15.06	58	33.20	28.50	29.56		
30	19.20	14.50	15.56	59	33.70	29.00	30.06		
31	19.70	15.00	16.06	60	34.20	29.50	30.56		
32	20.20	15.50	16.56						

QUALITY SYMBOLS MAJOR Ⓜ CRITICAL Ⓢ	DRAWN BY Xu,JinJun DATE 21/06/28		
GENERAL TOLERANCES (UNLESS SPECIFIED)	CHECKED BY Xu,ZhiYong DATE 21/06/28		
X. ±0.5 .X ±0.25 .XX ±0.15 .XXX ±0.1 ANGLES ±2°	APPROVED BY Xu,ZhiYong DATE 21/06/28	TITLE 0.5mm PITCH EASY ON FPC/FPC CONN.	
	UNITS mm	SIZE A4	RFQ NO. N/A
	SCALE 5:1	SHEET NO. 1 OF 1	DWG NO. 50671-XXXX-XXX

单击下面可查看定价，库存，交付和生命周期等信息

[>>ACES\(宏致\)](#)