

1.00mm Pitch FFC/FPC - F518/F519 Series

RIGHT ANGLE NON ZIF FLEX **CONNECTORS**

F518/F519 series are 1.00mm pitch right angle Non-ZIF flex connectors with surface mount termination and no locking mechanism. These connectors feature a height of 3.00mm and come in 4 to 30 contacts. These series feature a cable thickness of 0.30mm and provide enhanced durability of 30 mating cycles. The connectors come with a robust design and prevent solder and flux wicking. These are ideal for automotive, data, industrial, communication, consumer and medical applications

- Single action low-force FFC/ FPC insertion and removal
- High solderability and durability



FEATURES

- Non-ZIF (Zero Insertion Force) mechanism requires some force for insertion
- No locking mechanism
- Design against solder and flux wicking
- High temperature thermoplastic housing
- 4 to 30 positions available
- · Lead and halogen-free

BENEFITS

- Single action low-force FFC/FPC insertion and removal
- Ensures high solderability
- Wide operating temperature range of -40°C to +105°C
- Comprehensive range to satisfy different customer requirements
- Meets environmental, health and safety requirements

TECHNICAL INFORMATION

MATERIAL

Housing: LCP, black color(UL94V-0)

Contact: Phosphor bronze, T=0.25mm

Anchor-plate: Brass, T=0.20mm

MECHANICAL PERFORMANCE

FFC/FPC Retention Force: 30gf/terminal

■ Anchor-plate Retention Force: 300gf/plate min.

• Durability: 30 mating cycles

ELECTRICAL PERFORMANCE

Voltage Rating: 50V AC/DC

Current Rating: 0.5A

Contact Resistance: 30MΩ max.

• Insulation Resistance: 500M Ω min.

• Dielectric Withstanding Voltage: No short or breakdown after 500V AC, 2mA, 1min.

PACKAGING

■ Tape & Reel

APPROVALS AND CERTIFICATIONS

• UL file number E106764

RoHS compliant

SPECIFICATION

Aorora Product Specification: IS.EQC.005

ENVIRONMENTAL

■ Operating Temperature Range: -40°C to +105°C

TARGET MARKETS/APPLICATIONS



Car Multimedia Car Navigation Dashboard PND



Base Station Power **Switches**



Notebook **Tablets** Wearables Gaming DSC LCD & PDP TV



Router Server ODD HDD




Sensing element Monitoring camera Human Machine Interface Industrial PC Robotics

Ultrasonic Patient Monitor MRI CTInfusion Pump

≥ 1.00mm Pitch FFC/FPC – F518/F519 Series

PART NUMBER SELECTOR



单击下面可查看定价,库存,交付和生命周期等信息

>>Amphenol(安费诺)