



Cement Power Resistors (RoHS Compliant)

CR-RC Series

FEATURES


- Temperature Range: -55°C ~ +155°C
- 5% tolerance
- Exceptionally small, sturdy, and reliable
- Sealed with a special cement
- Excellent moisture resistance
- High temperature stability
- Ceramic flame retardant package
- Recommended wash method is alcohol




RoHS Compliant




HEAT RISE CHART




DERATING CURVE



PART NUMBERING SYSTEM



SERIES, WATTAGE, VALUE-RANGE, AND DIMENSIONS



| Series | Watts (W) | Value Ranges (Ω) | | Dimensions (mm) | | | | |
|--------|-----------|------------------|-------------|-----------------|------|------|------|---------|
| | | Wire Wound | Metal Oxide | L ±1 | W ±1 | H ±1 | l ±5 | d ±0.05 |
| CR | 5 | 0.1 ~ 47 | 48 ~ 25K | 22 | 10 | 9 | 35 | 0.75 |
| CR | 10 | 0.1 ~ 910 | 911 ~ 25K | 49 | 10 | 9 | 35 | 0.75 |
| CR | 15 | 1 ~ 1K | -- N/A -- | 49 | 12.5 | 11.5 | 35 | 0.75 |
| CR | 25 | 2 ~ 1.0K | -- N/A -- | 64 | 14.5 | 13.5 | 35 | 0.75 |

STANDARD STOCKED VALUES (Ω)


| | | | | | | | | | | | | | | | | | | | | | |
|------|------|------|-----|-----|-----|-----|-----|----|----|----|----|----|-----|-----|-----|-----|-----|------|------|------|------|
| 0.1 | 0.33 | 0.56 | 1.0 | 1.8 | 3.3 | 4.7 | 6.8 | 11 | 18 | 27 | 43 | 62 | 100 | 160 | 250 | 390 | 560 | 910 | 1.5K | 2.4K | 4.7K |
| 0.15 | 0.39 | 0.62 | 1.1 | 2.0 | 3.6 | 5.0 | 7.5 | 12 | 20 | 30 | 47 | 68 | 110 | 180 | 270 | 430 | 620 | 1.0K | 1.6K | 2.7K | 5.0K |
| 0.2 | 0.43 | 0.68 | 1.2 | 2.2 | 3.9 | 5.1 | 8.2 | 13 | 22 | 33 | 50 | 75 | 120 | 200 | 300 | 470 | 680 | 1.1K | 1.8K | 3.0K | 10K |
| 0.22 | 0.47 | 0.75 | 1.3 | 2.4 | 4.0 | 5.6 | 9.1 | 15 | 24 | 36 | 51 | 82 | 130 | 220 | 330 | 500 | 750 | 1.2K | 2.0K | 3.3K | 20K |
| 0.27 | 0.5 | 0.82 | 1.5 | 2.7 | 4.3 | 6.2 | 10 | 16 | 25 | 39 | 56 | 91 | 150 | 240 | 360 | 510 | 820 | 1.3K | 2.2K | 3.9K | 25K |
| 0.3 | 0.51 | 0.91 | 1.6 | 3.0 | | | | | | | | | | | | | | | | | |

*Other values available by special request



CONSTRUCTION

| No. | Subpart Name | Material | Material Generic Name |
|-----|-------------------|--|---|
| 1 | Body | Rod Type Ceramics | Al ₂ O ₃ , SiO ₂ |
| 2 | End Cap | Tin plated iron surface | Tin : 5%, Iron : 95% |
| 3 | Lead | Annealed copper wire (Electrosolder plated surface) Pb Free | Tin-Coated Copper wire |
| 4 | Ceramic Case | Ceramic | Al ₂ O ₃ , SiO ₂ |
| 5 | Resistance wire | Ni-Cr Alloy | Ni-Cr Alloy |
| 6 | Filling Materials | Quartz mixed sand | SiO ₂ |



Cement: Wire wound

CHARACTERISTICS

| Characteristics | Limits | | Test Methods (JIS C 5201-1) | | | | | | | | | | | | | | | |
|---------------------------------|---|----------------------|---|------|-------------|------|---|---------------|---------|---|------------|--------------|---|----------------|---------|---|------------|--------------|
| Temperature coefficient | ± 350 PPM / °C Max. <20Ω ± 400 PPM / °C | | 5.2 Natural resistance change per temp. degree centigrade. R ₂ -R ₁ ———— x10 ⁶ (PPM / °C) R ₁ (t ₂ -t ₁) R ₁ : Resistance value at room temperature (t ₁) R ₂ : Resistance value at room temp. plus 100 °C (t ₂) | | | | | | | | | | | | | | | |
| Dielectric withstanding voltage | No evidence of flashover, mechanical damage, arcing or insulation break down | | 5.7 Resistors shall be clamped in the trough of a 90° metallic V-block and shall be tested at AC potential respectively for 60 +10/ -0 secs. | | | | | | | | | | | | | | | |
| Temperature cycling | Resistance change rate is ± (2% + 0.05Ω) Max. with no evidence of mechanical damage | | 7.4 Resistance change after continuous 5 cycles for duty shown below: <table border="1"> <thead> <tr> <th>Step</th> <th>Temperature</th> <th>Time</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>-55 °C ± 3 °C</td> <td>30 mins</td> </tr> <tr> <td>2</td> <td>Room temp.</td> <td>10 ~ 15 mins</td> </tr> <tr> <td>3</td> <td>+155 °C ± 2 °C</td> <td>30 mins</td> </tr> <tr> <td>4</td> <td>Room temp.</td> <td>10 ~ 15 mins</td> </tr> </tbody> </table> | Step | Temperature | Time | 1 | -55 °C ± 3 °C | 30 mins | 2 | Room temp. | 10 ~ 15 mins | 3 | +155 °C ± 2 °C | 30 mins | 4 | Room temp. | 10 ~ 15 mins |
| Step | Temperature | Time | | | | | | | | | | | | | | | | |
| 1 | -55 °C ± 3 °C | 30 mins | | | | | | | | | | | | | | | | |
| 2 | Room temp. | 10 ~ 15 mins | | | | | | | | | | | | | | | | |
| 3 | +155 °C ± 2 °C | 30 mins | | | | | | | | | | | | | | | | |
| 4 | Room temp. | 10 ~ 15 mins | | | | | | | | | | | | | | | | |
| Short time overload | Resistance change rate is ± (5% + 0.05Ω) Max. with no evidence of mechanical damage | | 5.5 Permanent resistance change after the application of a potential of 2.5 times RCWV for 5 seconds | | | | | | | | | | | | | | | |
| Load life in humidity | Resistance value Wire-wound | Δ R/R ± 5% | 7.9 Resistance change after 1,000 hours operating at RCWV with duty cycle of (1.5 hours "on", 0.5 hour "off") in a humidity test chamber controlled at 40 °C ± 2 °C and 90 to 95 % relative humidity | | | | | | | | | | | | | | | |
| Load life | Resistance value Wire-wound | Δ R/R ± 5% | 7.10 Permanent resistance change after 1,000 hours operating at RCWV with duty cycle of (1.5 hours "on", 0.5 hour "off") at 70 °C ± 2 °C | | | | | | | | | | | | | | | |
| Terminal strength | No evidence of mechanical damage | | 6.1 Direct load : Resistance to a 2.5 kgs direct load for 10 secs. in the direction of the longitudinal axis of the terminal leads Twist test : Terminal leads shall be bent through 90 ° at a point of about 6mm from the body of the resistor and shall be rotated through 360° about the original axis of the bent terminal in alternating direction for a total of 3 rotations | | | | | | | | | | | | | | | |
| Resistance to soldering heat | Resistance change rate is ± (1% + 0.05Ω) Max. with no evidence of mechanical damage | | 6.4 Permanent resistance change when leads immersed to 3.2 to 4.8 mm from the body in 350 °C ± 10 °C solder for 3 ± 0.5 secs. | | | | | | | | | | | | | | | |
| Solderability | 95 % coverage Min. | | 6.5 The area covered with a new , smooth clean , shiny and continuous surface free from concentrated pinholes. Test temp. of solder : 245 °C ± 3 °C Dwell time in solder : 2 ~ 3 seconds | | | | | | | | | | | | | | | |

单击下面可查看定价，库存，交付和生命周期等信息

[>>Xicon](#)