

SCOPE :

This specification applies to the Pb Free high current type SMD inductors for
MSCDRI-105R-SERIES


PRODUCT IDENTIFICATION

MSCDRI - 105R - 100 M

① ② ③ ④

- ① Product Code
- ② Dimensions Code
- ③ Inductance Code
- ④ Tolerance Code

(1) SHAPES AND DIMENSIONS



A:	10.0±0.5	mm
B:	10.1±0.5	mm
C:	5.10 Max.	mm
D:	1.20 Typ.	mm
E:	7.70 Typ.	mm
F:	3.00 Typ.	mm

(2) ELECTRICAL SPECIFICATIONS

SEE TABLE 1

TEST INSTRUMENTS

- L : HP 4284A PRECISION LCR METER (or equivalent)
- RDC : CHROMA MODEL 16502 MILLIOHMETER (or equivalent)

(3) CHARACTERISTICS

- (3)-1 Ambient temperature +60°C Max.
- (3)-2 Operate temperature range -40°C ~ +125°C
(Including self temp. rise)
- (3)-3 Storage temperature range -40°C ~ +125°C



MAG.LAYERS

TABLE 1

MAGLAYERS PT/NO.	Inductance L(μH)	Percent Tolerance	Test Frequency	Resistance RDC(Ω)Max.	Rated DC Current		Marking
					IDC1(A)	IDC2(A)	
MSCDRI-105R-1R5□	1.5	N	100kHz/0.25V	5.8m	10.5	8.30	1R5
MSCDRI-105R-2R2□	2.2	M,N	100kHz/0.25V	7.2m	9.25	7.50	2R2
MSCDRI-105R-3R3□	3.3	N	100kHz/0.25V	10.4m	7.80	6.50	3R3
MSCDRI-105R-4R7□	4.7	M,N	100kHz/0.25V	12.3m	6.40	6.10	4R7
MSCDRI-105R-6R8□	6.8	N	100kHz/0.25V	18m	5.40	5.40	6R8
MSCDRI-105R-8R2□	8.2	M,N	100kHz/0.25V	20m	4.85	5.00	8R2
MSCDRI-105R-100□	10	M,N	100kHz/0.25V	26m	4.45	4.50	100
MSCDRI-105R-120□	12	M,N	100kHz/0.25V	33m	4.00	3.80	120
MSCDRI-105R-150□	15	M,N	100kHz/0.25V	41m	3.60	3.40	150
MSCDRI-105R-180□	18	M,N	100kHz/0.25V	46m	3.20	3.10	180
MSCDRI-105R-220□	22	M,N	100kHz/0.25V	61m	2.95	2.90	220
MSCDRI-105R-270□	27	M,N	100kHz/0.25V	69m	2.70	2.60	270
MSCDRI-105R-330□	33	M,N	100kHz/0.25V	84m	2.40	2.50	330
MSCDRI-105R-390□	39	M,N	100kHz/0.25V	0.106	2.30	2.25	390
MSCDRI-105R-470□	47	M,N	100kHz/0.25V	0.130	2.00	2.00	470
MSCDRI-105R-560□	56	M,N	100kHz/0.25V	0.149	1.90	1.90	560
MSCDRI-105R-680□	68	M,N	100kHz/0.25V	0.201	1.65	1.60	680
MSCDRI-105R-820□	82	M,N	100kHz/0.25V	0.227	1.50	1.45	820
MSCDRI-105R-101□	100	K,M	100kHz/0.25V	0.253	1.35	1.35	101
MSCDRI-105R-121□	120	K,M	100kHz/0.25V	0.303	1.28	1.18	121
MSCDRI-105R-151□	150	K,M,N	100kHz/0.25V	0.370	1.12	1.10	151
MSCDRI-105R-181□	180	K,M	100kHz/0.25V	0.419	1.04	1.00	181
MSCDRI-105R-221□	220	K,M	100kHz/0.25V	0.500	0.94	0.94	221
MSCDRI-105R-271□	270	K,M	100kHz/0.25V	0.672	0.84	0.80	271
MSCDRI-105R-331□	330	K,M	100kHz/0.25V	0.812	0.75	0.73	331
MSCDRI-105R-391□	390	K,M	100kHz/0.25V	0.953	0.70	0.70	391
MSCDRI-105R-471□	470	K,M	100kHz/0.25V	1.289	0.60	0.54	471
MSCDRI-105R-561□	560	K,M	100kHz/0.25V	1.430	0.54	0.52	561
MSCDRI-105R-681□	680	K,M	100kHz/0.25V	1.599	0.52	0.51	681
MSCDRI-105R-821□	820	K,M	100kHz/0.25V	1.768	0.50	0.48	821
MSCDRI-105R-102□	1000	K,M	100kHz/0.25V	1.989	0.48	0.42	102


※ □ specify the inductance tolerance, K(±10%), M(±20%), N(±30%)

※ IDC1 : Based on inductance change ($\Delta L/L_0 : \leq \text{drop } 35\%$) @ambient temperature 25°C

IDC2 : Based on temperature rise ($\Delta T : 40^\circ\text{C TYP.}$)

Rated DC Current : The less value which is IDC1 or IDC2.

(4) RELIABILITY TEST METHOD MECHANICAL

TEST ITEM	SPECIFICATION	TEST DETAILS
Substrate bending	$\Delta L/L_0 \leq \pm 5\%$ There shall be no mechanical damage or electrical damage.	<p>The sample shall be soldered onto the printed circuit board in figure 1 and a load applied until the figure in the arrow direction is made approximately 3mm.(keep time 30 seconds)</p> <p>PCB dimension shall the page 7/9</p> <p>F(Pressurization)</p>  <p>PRESSURE ROD figure-1</p>
Vibration	$\Delta L/L_0 \leq \pm 5\%$ There shall be no mechanical damage.	<p>The sample shall be soldered onto the printed circuit board and when a vibration having an amplitude of 1.52mm and a frequency of from 10 to 55Hz/1 minute repeated should be applied to the 3 directions (X,Y,Z) for 2 hours each. (A total of 6 hours)</p>
Solderability	New solder More than 90%	<p>Flux (rosin, isopropyl alcohol{JIS-K-1522}) shall be coated over the whole of the sample before hard, the sample shall then be preheated for about 2 minutes in a temperature of 130~150°C and after it has been immersed to a depth 0.5mm below for 3±0.2 seconds fully in molten solder M705 with a temperature of 245±5°C.</p> <p>More than 90% of the electrode sections shall be covered with new solder smoothly when the sample is taken out of the solder bath.</p>

MECHANICAL

TEST ITEM	SPECIFICATION	
Resistance to Soldering heat (reflow soldering)	There shall be no damage or problems.	<p style="text-align: center;">Temperature profile of reflow soldering</p> <p>The graph shows the temperature profile for reflow soldering. The y-axis is 'Soldering temperature (°C)' ranging from 50 to 300. The x-axis represents time. The profile starts at 50°C, rises to 150°C, and remains there for 2 minutes (Pre-heating). It then rises to a peak of 260±3°C for 10 seconds (Soldering). It then drops to 230°C and remains there for a minimum of 30 seconds (30 sec Min (230°C)). Finally, it cools down slowly (Slow cooling) to room temperature. The cooling phase is labeled 'Slow cooling (Stored at room temperature)'. The total time for the soldering phase is 10 seconds, and the cooling phase is 2 minutes or more.</p> <p>The specimen shall be passed through the reflow oven with the condition shown in the above profile for 1 time.</p> <p>The specimen shall be stored at standard atmospheric conditions for 1 hour, after which the measurement shall be made.</p>

ELECTRICAL

TEST ITEM	SPECIFICATION	TEST DETAILS
Insulation resistance	There shall be no other damage or problems.	DC 100V voltage shall be applied across this sample of top surface and the terminal. The insulation resistance shall be more than $1 \times 10^8 \Omega$.
Dielectric withstand voltage	There shall be no other damage or problems.	AC 100V voltage shall be applied for 1 minute across the top surface and the terminal of this sample
Temperature characteristics	$\Delta L/L20^\circ\text{C} \leq \pm 10\%$ $0 \sim 2000 \text{ ppm}/^\circ\text{C}$	The test shall be performed after the sample has stabilized in an ambient temperature of -20 to $+85^\circ\text{C}$, and the value calculated based on the value applicable in a normal temperature and normal humidity shall be $\Delta L/L20^\circ\text{C} \leq \pm 10\%$.

ENVIROMENT CHARACTERISTICS


TEST ITEM	SPECIFICATION																
High temperature storage	$\Delta L/L_0 \leq \pm 5\%$ There shall be no mechanical damage.	The sample shall be left for 96 ± 4 hours in an atmosphere with a temperature of $85 \pm 2^\circ\text{C}$ and a normal humidity. Upon completion of the measurement shall be made after the sample has been left in a normal temperature and normal humidity for 1 hour.															
Low temperature storage	$\Delta L/L_0 \leq \pm 5\%$ There shall be no mechanical damage.	The sample shall be left for 96 ± 4 hours in an atmosphere with a temperature of $-25 \pm 3^\circ\text{C}$. Upon completion of the test, the measurement shall be made after the sample has been left in a normal temperature and normal humidity for 1 hour.															
Change of temperature	$\Delta L/L_0 \leq \pm 5\%$ There shall be no other damage of problems	The sample shall be subject to 5 continuous cycles, then it shall be subjected to standard atmospheric conditions for 1 hour, after which measurement shall be made. <div style="text-align: center;"> table 2 <table border="1" style="margin: auto;"> <thead> <tr> <th></th> <th style="text-align: center;">Temperature</th> <th style="text-align: center;">Duration</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;">1</td> <td style="text-align: center;">$-25 \pm 3^\circ\text{C}$ (Thermostat No.1)</td> <td style="text-align: center;">30 min.</td> </tr> <tr> <td style="text-align: center;">2</td> <td style="text-align: center;">Standard atmospheric</td> <td style="text-align: center;">No.1→No.2</td> </tr> <tr> <td style="text-align: center;">3</td> <td style="text-align: center;">$85 \pm 2^\circ\text{C}$ (Thermostat No.2)</td> <td style="text-align: center;">30 min.</td> </tr> <tr> <td style="text-align: center;">4</td> <td style="text-align: center;">Standard atmospheric</td> <td style="text-align: center;">No.2→No.1</td> </tr> </tbody> </table> </div>		Temperature	Duration	1	$-25 \pm 3^\circ\text{C}$ (Thermostat No.1)	30 min.	2	Standard atmospheric	No.1→No.2	3	$85 \pm 2^\circ\text{C}$ (Thermostat No.2)	30 min.	4	Standard atmospheric	No.2→No.1
	Temperature	Duration															
1	$-25 \pm 3^\circ\text{C}$ (Thermostat No.1)	30 min.															
2	Standard atmospheric	No.1→No.2															
3	$85 \pm 2^\circ\text{C}$ (Thermostat No.2)	30 min.															
4	Standard atmospheric	No.2→No.1															
Moisture storage	$\Delta L/L_0 \leq \pm 5\%$ There shall be no mechanical damage.	The sample shall be left for 96 ± 4 hours in a temperature of $40 \pm 2^\circ\text{C}$ and a humidity(RH) of 90~95%. Upon completion of the test, the measurement shall be made after the sample has been left in a normal temperature and normal humidity more than 1 hour.															
Test conditions : <p style="text-align: center;">The sample shall be reflow soldered onto the printed circuit board in every test.</p>																	

(5) LAND DIMENSION (Ref.)


PCB: GLASS EPOXY $t=1.6\text{mm}$

(5)-1 LAND PATTERN DIMENSIONS

(STANDARD PATTERN) Unit:mm




(5)-2 SUBSTRATE BENDING TEST BENDING TEST BOARD




(6) PACKAGING


(6)-1 CARRIER TAPE DIMENSIONS (mm)



(6)-2 TAPING DIMENSIONS (mm)



(6)-3 REEL DIMENSIONS (mm)



(6)-4 QUANTITY

700pcs/Reel

The products are packaged so that no damage will be sustained.

单击下面可查看定价，库存，交付和生命周期等信息

[>>MAG. LAYERS](#)