

## FEATURES

- | Size Design  $\Phi 8.0 \times 6.0 \text{mm}$

---

- | High Current Handling Capability 10,000A @ 8/20  $\mu\text{s}$

---

- | Low Capacitance and Insertion Loss

---

- | Quick Response and Long Service Life

---

- | Moisture sensitivity level: Level 1



$\Phi 8.0 \times 6.0 \text{mm}$



Schematic Symbol

## APPLICATION INFORMATION

- | Communication equipment.

---

- | Repeaters, Modems


---

- | Telephone Interface, Line cards.

---

- | Data communication equipment.

## AGENCY APPROVALS

| Icon  | Solderability                      |
|---|------------------------------------|
| RoHS  | Compliance with 2011/65/EU         |
| HF  | Compliance with IEC61249-2-21:2003 |
|  | Mean lead free                     |
|  | UL Certificated E505857            |

## PRODUCT CHARACTERISTICS

| Lead Material         | Body Material | Terminal Finish       |
|-----------------------|---------------|-----------------------|
| Copper or Fe-Ni alloy | Ceramics      | 100% Matte-Tin Plated |

## ELECTRICAL PARAMETER

| Parameter                         | Symbol                    | Limit                                      | Unit         |
|-----------------------------------|---------------------------|--|--------------|
| DC Blocking Voltage 1)            | 100V/s                    | 480-720                                    | V            |
| Impulse Spark-over Voltage        | At 1kV/ $\mu$ s           | for 99 % of measured values $\leq$ 1400    | V            |
|                                   | At 1kV/ $\mu$ s           | Typical values of distribution $\leq$ 1300 | V            |
| Impulse Discharge Current 2)      | 8/20 $\mu$ s $\pm$ 5times | 10   | KA           |
| Insulation Resistance             | DC=100V                   | $\geq$ 1                                   | G $\Omega$   |
| Capacitance at 1MHz               | V <sub>DC</sub> =0.5V     | $\leq$ 1.5                                 | pF           |
| Operating and Storage Temperature |                           | -40~125                                    | $^{\circ}$ C |


1) In ionized mode

2) Terms and waveforms in accordance with ITU-T Rec. K. 12; IEC 61643-21

## ENVIRONMENTAL RELIABILITY CHARACTERISTICS


| Testing items                 | Technical standards   |
|-------------------------------|---|
| High Temperature Storage Test | Temperature: 125 $^{\circ}$ C ; Time:2H                                 |
| Low Temperature Storage Test  | Temperature: -40 $^{\circ}$ C ; Time:2H                                 |
| Vibration                     | Frequency: 10-500Hz ; Amplitude: 0.15mm ; Time:45min                    |
| Resistance of soldering heat  | Temperature: 260 $\pm$ 5 $^{\circ}$ C; Time of dip soldering: 10s,1time |

## PRODUCT DIMENSIONS




| Ref | Outline Dimensions   |
|-----|----------------------|
|     | Millimeters          |
| A   | 62 $\pm$ 2           |
| B   | 6 $\pm$ 0.2          |
| C   | $\Phi$ 8.0 $\pm$ 0.2 |
| D   | $\Phi$ 0.8           |

## WAVE SOLDERING




| Wave Parameter         |                  | Lead-free assembly |
|------------------------|------------------|--------------------|
| Pre Heat               | Temperature Min  | 100°C              |
|                        | Temperature Max  | 150°C              |
|                        | Time(min to max) | 60 – 180 secs      |
| Solder pot Temperature |                  | 280°C Max          |
| Solder Dwell Time      |                  | 2-5 seconds        |

## TAPE AND REEL SPECIFICATION



| Ref. | Dimensions  |             |
|------|-------------|-------------|
|      | Millimeters | Inches      |
| W    | 65±2        | 2.559±0.079 |
| A0   | 10±0.5      | 0.394±0.020 |
| B0   | 6±1         | 0.236±0.012 |
| K0   | 1.2 Max.    | 0.47 Max.   |
| D    | 2.5±0.5     | 0.098±0.020 |
| F    | 340±2       | 13.39±0.079 |
| E    | 73±2        | 2.874±0.079 |
| P    | 82±2        | 3.228±0.079 |
| P0   | Φ16±1       | Φ0.63±0.039 |

## ORDERING INFORMATION

| Part Number | Size       | Marking  | Qty/pcs |        |
|-------------|------------|--|---------|--------|
|             |            |  | Reel    | Carton |
| SG2R08B600  | Φ8.0*6.0mm |  SG600 08 | 1000    | 4000   |

**Headquarters**

No.3387 Shendu Road Pujiang  
I&E Park  
Minhang Shanghai China  
201000

**Hotline**

400-021-5756

**Web**

<https://www.semiware.com>

**Sales Center**

Tel: 86-21-3463-7458  
Email: [sales18@semiware.com](mailto:sales18@semiware.com)

**Customer Service**

Tel: 86-21-5484-1001  
Email: [sales17@semiware.com](mailto:sales17@semiware.com)

**Technical Support**

Tel: 86-21-3463-7654  
Email: [fae01@semiware.com](mailto:fae01@semiware.com)

**Complaint & Suggestions**

Tel: 86-21-3463-7172  
Ext: 8868  
Email: [cs03@semiware.com](mailto:cs03@semiware.com)

**By QR Code**

Website



Wechat

To find your local partner within Semiware's global network: [www.semiware.com](http://www.semiware.com)

© 2022 Semiware Semiconductor Inc.

The content of this document has been carefully checked and understood. However, neither Semiware nor its subsidiaries assume any liability whatsoever for any errors or inaccuracies of this document and the consequences thereof. Published specifications are subject to change without notice. Product suitability for any area of application must ultimately be determined by the customer. In all cases, products must never be operated outside their published specifications. Semiware does not guarantee the availability of all published products. This disclaimer shall be governed by substantive Chinese law and resulting disputes shall be settled by the courts at the place of business of Semiware. Latest publications and a complete disclaimer can be downloaded from the Semiware website. All trademarks recognized.

单击下面可查看定价，库存，交付和生命周期等信息

[>>SEMIWARE\(赛米微尔\)](#)