

LBTN180D3T1G

S-LBTN180D3T1G

NPN power transistors

1. FEATURES

- High current
- High power dissipation capability
- We declare that the material of product compliance with RoHS requirements and Halogen Free.
- S- prefix for automotive and other applications requiring unique site and control change requirements; AEC-Q101 qualified and PPAP capable.

2. APPLICATIONS


- Linear voltage regulators
- Low-side switches
- Battery-driven devices
- Power management
- MOSFET drivers
- Amplifiers

3. DEVICE MARKING AND ORDERING INFORMATION


Device	Marking	Shipping
LBTN180D3T1G	N3	4000/Tape&Reel

4. MAXIMUM RATINGS(Ta = 25°C)

Parameter	Symbol	Limits	Unit
Collector–Emitter Voltage	V _{CEO}	85	V
Collector–Base Voltage	V _{CBO}	105	V
Emitter–Base Voltage	V _{EBO}	6	V
Collector Current	I _C	1	A
Peak collector current(tp ≤ 1 ms)	I _{CM}	2	A
Base current	I _B	0.3	A
Peak base current(tp ≤ 1 ms)	I _{BM}	0.3	A
Junction temperature	T _J	150	°C
Storage temperature	T _{stg}	-65~+150	°C







DFN2020-3






5. ELECTRICAL CHARACTERISTICS (Ta= 25°C)

Characteristic	Symbol	Min.	Typ.	Max.	Unit
Collector–Emitter Breakdown Voltage (IC = 1 mA, IB = 0)	VBR(CEO)	85	-	-	V
Collector–Base Breakdown Voltage (IC = 100 μA, IE = 0)	VBR(CBO)	105	-	-	V
Emitter–Base Breakdown Voltage (IE = 100 μA, IC = 0)	VBR(EBO)	6	-	-	V
Collector Cutoff Current (VCB = 30 V, IE = 0 A)	ICBO	-	-	100	nA
Emitter Cut-off Current (VEB = 5V, IC = 0)	IEBO	-	-	100	nA
Collector-Emitter cutoff Current (VCE = 80V, IB = 0)	ICEO	-	-	5	μA
DC Current Gain (VCE = 2 V, IC = 5 mA) (VCE = 2 V, IC = 150 mA) (VCE = 2 V, IC = 500 mA)	HFE	63 63 40	- - -	- 250 -	
Collector–Emitter Saturation Voltage (IC = 500 mA, IB = 50 mA)	VCE(sat)	-	-	0.5	V
Base-Emitter voltage (VCE = 2 V, IC = 500 mA)	VBE	-	-	1	V
Transition Frequency (VCE = 5 V, IC = 50 mA, f = 100 MHz)	fT	100	-	-	MHz
Collector Capacitance (VCB = 10 V, IE = ie = 0 A, f = 1 MHz)	Cc	-	6	-	pF


6.ELECTRICAL CHARACTERISTICS CURVES



6.ELECTRICAL CHARACTERISTICS CURVES(Con.)




7. OUTLINE AND DIMENSIONS



DFN2020-3			
Dim	Min.	Typ.	Max.
A	0.60	0.65	0.70
A1	0.00	0.02	0.05
A3	0.152REF.		
D	1.95	2.00	2.05
E	1.95	2.00	2.05
D1	1.45	1.50	1.55
E1	0.95	1.00	1.05
b	0.25	0.30	0.35
e	1.30TYP.		
k	0.20	0.25	0.30
L	0.35	0.40	0.45

All Dimensions in mm

8. SOLDERING FOOTPRINT



DFN2020-3	
Dim	(mm)
X	1.60
Y	2.00
b1	0.35
b2	0.45
L	0.50
Y1	1.10
k	0.15
e	1.30

DISCLAIMER

- Curve guarantee in the specification. The curve of test items with electric parameter is used as quality guarantee. The curve of test items without electric parameter is used as reference only.
- Before you use our Products for new Project, you are requested to carefully read this document and fully understand its contents. LRC shall not be in any way responsible or liable for failure, malfunction or accident arising from the use of any LRC's Products against warning, caution or note contained in this document.
- All information contained in this document is current as of the issuing date and subject to change without any prior notice. Before purchasing or using LRC's Products, please confirm the latest information with a LRC sales representative.

单击下面可查看定价，库存，交付和生命周期等信息

[>>LRC\(乐山无线电\)](#)