

DATA SHEET

SHUNT RESISTOR AUTOMOTIVE GRADE

PW series

5%, 1%

Sizes

2512/ 3921/ 5931

RoHS compliant & Halogen free

Preliminary



SCOPE

This specification describes shunt resistor PW series made by welding technology.

APPLICATIONS

- Power
- Telecom base station
- Automotive (Headlight/ Window control/ Engine control unit/ Steering control...)
- Alternative energy

FEATURES

- AEC-Q200 qualified
- Total lead free without RoHS exemption
- Welding metal plate construction
- Resistance value down to 0.0001Ω and high power up to 15W

ORDERING INFORMATION - GLOBAL PART NUMBER

Global part numbers are identified by the series, size, tolerance, packing type, temperature coefficient, taping reel and resistance value.

GLOBAL PART NUMBER

PW XXXX X X X XX XXXX L
 (1) (2) (3) (4) (5) (6) (7)

(1) SIZE

2512/ 3921/ 5931

(2) TOLERANCE

F = ±1% J = ±5%

(3) PACKAGING TYPE

K = Embossed taping reel

(4) TEMPERATURE COEFFICIENT OF RESISTANCE

- E = ±50 ppm/°C
- M = ±75 ppm/°C
- F = ±100 ppm/°C
- L = ±150 ppm/°C
- N = ±175 ppm/°C
- G = ±200 ppm/°C
- H = ±225 ppm/°C

(5) TAPING REEL

- I3 = 13 inch Dia. reel, standard power, 3W for 2512, 3921 and 5931, 5W
- P4 = 4W, 13 inch Dia. Reel
- P5 = 5W, 13 inch Dia. Reel
- P6 = 6W, 13 inch Dia. Reel
- P7 = 7W, 13 inch Dia. Reel
- P8 = 8W, 13 inch Dia. Reel
- P9 = 9W, 13 inch Dia. Reel
- PA = 10W, 13 inch Dia. Reel
- PB = 15W, 13 inch Dia. Reel

(6) RESISTANCE VALUE

0.1mΩ to 5mΩ
 There are 3~5 digits indicated the resistance value. Letter R/ U is decimal point.
 Detailed coding rules of resistance are shown in the table of "Resistance rule of global part number".

(7) DEFAULT CODE

Letter L is the system default code for ordering only. (Note)

Resistance code rule	Example
0RXXX	0R001 = 1 mΩ
0UX	0U2 = 0.2 mΩ

ORDERING EXAMPLE


The ordering code of a PW3921, value 0.0005Ω with ±1% tolerance, 9W and TCR 75 ppm supplied in 13-inch tape reel is : PW3921FKMP90U5L

NOTE

- 1. All our RSMD products are RoHS compliant. "LFP" of the internal 2D reel label mentions "Lead-Free Process"


MARKING

PW2512



No marking

PW3921/5931



No marking

OUTLINES AND DIMENSION




Table 1 For outlines, please refer to Fig. 2

TYPE	L (mm)	W (mm)	H (mm)	I1 (mm)
PW2512	6.35±0.25	3.18±0.25	0.40±0.15	1.14±0.25
PW3921	10.1±0.25	5.20±0.25	0.50±0.15	2.00±0.25
PW5931	15.0±0.25	7.75±0.25	0.50±0.13	4.00±0.25

Table 2

Resistance Value	0.1mΩ	0.2mΩ	0.25mΩ	0.3mΩ	0.4mΩ	0.5mΩ	0.7 mΩ	1 mΩ	1.5 mΩ	2 mΩ	3 mΩ	4 mΩ	5 mΩ
T (mm)	---	---	---	0.95±0.13	0.75±0.13	0.84±0.13	---	0.43±0.13	---	0.66±0.13	0.44±0.13	0.33±0.13	0.31±0.13
Thickness	---	1.35±0.13	1.05±0.13	1.35±0.13	1.05±0.13	0.86±0.13	0.60±0.13	0.43±0.13	0.92±0.13	0.72±0.13	0.48±0.13	0.36±0.13	0.25±0.13
	1.42±0.13	1.33±0.13	---	1.00±0.13	---	0.60±0.13	---	0.33±0.13	---	0.49±0.13	0.33±0.13	0.25±0.13	---

Remark: The thickness of products can be counted by H dimension + T dimension (mm) ± Tolerance 0.26 (mm)

ELECTRICAL CHARACTERISTICS




Fig. 4 Solder pad dimensions

Note: Series resistors are suitable for IR reflow soldering

Table 3 For outlines, please refer to Fig. 3

TYPE	A (mm)	B (mm)	C (mm)
PW2512	1.80±0.15	3.40±0.15	3.40±0.13
PW3921	2.75±0.25	6.20±0.25	5.60±0.13
PW5931	5.20±0.25	8.75±0.25	5.60±0.13

Table 4

SIZE	POWER RATING ⁽⁴⁾	OPERATING TEMP. RANGE	RESISTANCE RANGE	TOLERANCE ⁽²⁾	TEMPERATURE COEFFICIENT OF RESISTANCE ⁽³⁾
PW2512	3W(I3) 4W(P4)	-65°C to 170°C	0.3/ 0.4/ 0.5/ 1 / 2 / 3 / 4/ 5mΩ	±1% (F) ±5% (J)	±200ppm/°C (G): 0.3mΩ ±175ppm/°C (N): 0.4/0.5/1mΩ ±75ppm/°C (M): ≥2mΩ
	5W(P5)		0.3/ 0.4/ 0.5/1/ 2mΩ		
	6W(P6)		0.3/ 0.4/ 0.5/1mΩ		
PW3921	3W(I3) 5W(P5)	-65°C to 170°C	0.2/ 0.25/ 0.3/ 0.4/ 0.5/ 0.7mΩ 1/ 1.5/ 2 / 3/ 4/ 5mΩ	±1% (F) ±5% (J)	±150ppm/°C (L): 0.2/0.3mΩ ±75ppm/°C (M): ≥0.5mΩ ±50ppm/°C (E): ≥1mΩ
	6W(P6)		0.2/ 0.25/ 0.3/ 0.4/ 0.5/ 0.7mΩ 1/ 1.5/ 2mΩ		
	8W(P8)		0.2/ 0.25/ 0.3/ 0.4/ 0.5/ 0.7mΩ		
	9W(P9)				
	10W(PA)		0.2/ 0.25/ 0.3/ 0.4/ 0.5mΩ		
	12W(PC)				
PW5931	5W(I3) 7W(P7)	-65°C to 170°C	0.1/ 0.2/ 0.3/ 0.5mΩ 1 / 2 / 3 / 4mΩ	±1% (F) ±5% (J)	±225ppm/°C (H): 0.2mΩ ±175ppm/°C (N): ≥0.1mΩ ±100ppm/°C (F): ≥0.3mΩ ±75ppm/°C (M): ≥1mΩ ±50ppm/°C (E): ≥2mΩ
	9W(P9)		0.1/ 0.2/ 0.3/ 0.5mΩ 1mΩ		
	10W(PA)		0.1/ 0.2/ 0.3/ 0.5mΩ		
	15W(PB)		0.1/ 0.2mΩ		

Note: 1. Please contact with sales offices, distributors, and representatives in your region before ordering.

2. Global part number (code7)

3. Global part number (code 9)

4. Global part number (code 10-11) The shunt resistors' rated power is highly related to the combine heat equivalent from PCB and resistance element. It is recommended to consider design principles such as larger pad surfaces, increasing copper weights, etc., to keep the terminal under its thermal limit.

FUNCTIONAL DESCRIPTION

OPERATING TEMPERATURE RANGE

Temperature Range is
-65°C to +170°C (Fig.5)

POWER RATING

Standard rated power at 70°C:

- PW2512 = 3W
- PW3921 = 3W
- PW5931 = 5W

For detail power value, please refer to Table 4.

RATED VOLTAGE

The DC or AC (rms) continuous working voltage corresponding to the rated power is determined by the following formula:



$$V = \sqrt{(P \times R)}$$

or max. working voltage whichever is less
Where

V = Continuous rated DC or
AC (rms) working voltage (V)

P = Rated power (W)

R = Resistance value (Ω)



PACKING STYLE AND PACKAGING QUANTITY

Table 5 Packing style and packaging quantity

PACKING STYLE	REEL			
	DIMENSION	2512	3921	5931
Embossed taping reel (K)	13" (330 mm)	4,000	3,000	1,500

EMBOSSED TAPE




Fig. 7 Embossed Tape

Table 6 Dimensions of embossed tape for relevant chip resistors size

DIMENSION	A ₀	B ₀	D ₀	D ₁ MIN.	E	F	K ₀ MAX.	P ₀	P ₁	P ₂	T ₁ MAX.	T ₂ MAX.	T MAX.	W MAX.
PW2512														
0.3/ 0.4/ 0.5/ 2mΩ	3.58±0.1	6.70±0.1	1.5±0.1	1.5	1.75±0.1	5.5±0.1	1.52	4±0.1	8±0.1	2±0.1	0.1	1.92	0.30	12.3
1/ 3/ 4/ 5mΩ	3.58±0.1	6.70±0.1	1.5±0.1	1.5	1.75±0.1	5.5±0.1	1.14	4±0.1	8±0.1	2±0.1	0.1	1.54	0.30	12.3
PW3921														
0.2/ 0.25/ 0.3/ 0.4/ 0.5/ 0.7/ 1.5/ 2mΩ	5.59±0.1	10.41±0.1	1.5±0.1	1.5	1.75±0.1	7.5±0.1	2.13	4±0.1	8±0.1	2±0.1	0.1	2.64	0.41	16.3
1/ 3/ 4/ 5mΩ	5.59±0.1	10.41±0.1	1.5±0.1	1.5	1.75±0.1	7.5±0.1	1.14	4±0.1	8±0.1	2±0.1	0.1	1.65	0.41	16.3
PW5931														
≤0.3mΩ	8.3±0.1	15.62±0.1	1.5±0.1	1.5	1.75±0.1	11.5±0.1	2.39	4±0.1	12±0.1	2±0.1	0.1	2.90	0.41	24.3
≥0.5mΩ	8.3±0.1	15.62±0.1	1.5±0.1	1.5	1.75±0.1	11.5±0.1	1.22	4±0.1	12±0.1	2±0.1	0.1	1.73	0.41	24.3

Unit : mm

REEL SPECIFICATION




Fig. 8

Table 7 Dimensions of reel specification for relevant chip resistors size; see Fig. 7

PRODUCT SIZE CODE	REEL SIZE	SYMBOL					
		A	N	C	D	W1	W2 max.
PW2512	13" (Φ330mm)	330+0 /-3	100±0.5	13.5±0.5	21±0.8	13.0±0.3	17.5
PW3921	13" (Φ330mm)	330+0 /-3	100±0.5	13.5±0.5	21±0.8	16.4+2.0/-0	22.4
PW5931	13" (Φ330mm)	330+0 /-3	100±0.5	13.5±0.5	21±0.8	24.4+2.0/-0	30.4

Unit : mm

TESTS AND REQUIREMENTS

Table 8 Test condition, procedure and requirements

TEST	TEST METHOD	PROCEDURE	REQUIREMENTS
Short Time Overload	IEC 60115-1 8.1	5 times of rated power for 5 seconds at room temperature	$\pm(1\%+0.0005 \Omega)$ No visible damage
High Temperature Exposure	MIL-STD-202 method 108 IEC 60068-2-2	1,000 hours at maximum operating temperature depending on specification, unpowered,	$\pm(1\%+0.0005 \Omega)$
Temperature Cycling	JESD22-A104	-55/+155°C, 1000 cycles Dwell time is 15 minutes. Devices mounted Air – Air.	$\pm(1\%+0.0005 \Omega)$
Biased Humidity	MIL-STD-202 method 103	1,000 hours; 85 °C / 85% RH 10% of operating power	$\pm(1\%+0.0005 \Omega)$
Life/ Operational Life/ Endurance	MIL-STD-202 method 108 IEC 60115-1 7.1	1,000 hours at 70 °C applied rated power 1.5 hours on, 0.5 hour off, still air required	$\pm(1\%+0.0005 \Omega)$
Resistance to Soldering Heat	MIL-STD-202 method 210	Specimen passed 3 times reflow temperature at 260°C, with solder.	$\pm(0.5\%+0.0005 \Omega)$ No visible damage
Board Flex / Bending	AEC-Q200-005	Chips mounted on a glass epoxy resin PCB (FR4) Bending: 2 mm Holding time: minimum 60 seconds	$\pm(1\%+0.0005 \Omega)$
Vibration	MIL-STD-202 method 204	5 g's for 20 min., 12 cycles each of 3 orientations.	$\pm(1\%+0.0005 \Omega)$

REVISION HISTORY

REVISION	DATE	CHANGE NOTIFICATION	DESCRIPTION
----------	------	---------------------	-------------

Version 0	Dec. 14, 2023	-	-First issue of this specification
-----------	---------------	---	------------------------------------

LEGAL DISCLAIMER

YAGEO, its distributors and agents (collectively, "YAGEO"), hereby disclaims any and all liabilities for any errors, inaccuracies or incompleteness contained in any product related information, including but not limited to product specifications, datasheets, pictures and/or graphics. YAGEO may make changes, modifications and/or improvements to product related information at any time and without notice.

YAGEO makes no representation, warranty, and/or guarantee about the fitness of its products for any particular purpose or the continuing production of any of its products. To the maximum extent permitted by law, YAGEO disclaims (i) any and all liability arising out of the application or use of any YAGEO product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for a particular purpose, non -infringement and merchantability.

YAGEO products are designed for general purpose applications under normal operation and usage conditions. Please contact YAGEO for the applications listed below which require especially high reliability for the prevention of defects which might directly cause damage to the third party's life, body or property: Aerospace equipment (artificial satellite, rocket, etc.), Atomic energy-related equipment, Aviation equipment, Disaster prevention equipment, crime prevention equipment, Electric heating apparatus, burning equipment, Highly public information network equipment, data-processing equipment , Medical devices, Military equipment, Power generation control equipment, Safety equipment, Traffic signal equipment, Transportation equipment and Undersea equipment, or for any other application or use in which the failure of YAGEO products could result in personal injury or death, or serious property damage. Particularly **YAGEO Corporation and its affiliates do not recommend the use of commercial or automotive grade products for high reliability applications or manned space flight.**

Information provided here is intended to indicate product specifications only. YAGEO reserves all the rights for revising this content without further notification, as long as products are unchanged. Any product change will be announced by PCN.