

SEA&LAND ELECTRONIC CORP.

13F., No.120-10,
 Sec. 3, Zhongshan Rd., Zhonghe Dist., New Taipei City 235,
 Taiwan
 Tel.: 886-2-8221-2567
 Fax.: 886-2-2225-7268

Techfuse
PTC Devices
 Resettable Fuse

PRODUCT: nSMD025
 DOCUMENT: QR0429
 ECN. NO.:
 REV LETTER:
 REV DATE: 2013-4-2
 PAGE NO.: 1 of 1

Specification Sheet

Terminal Pad Solderability:
 Meets EIA Specification RS186-9E
 And ANSI/J-STD-002 Category 3.

Terminal Pad Materials:
 Tin-plated Nickel-Copper

Lead-Free, RoHS Compliant

Marking:

Part Identification

nSMD025 = αA




TABLE I. DIMENSIONS:

| Model | Marking | A | | B | | C | | D | E |
|---------|------------|------|------|------|------|------|------|------|------|
| | | Min. | Max. | Min. | Max. | Min. | Max. | Min. | Min. |
| nSMD025 | αA | 3.00 | 3.50 | 1.50 | 1.80 | 0.40 | 0.90 | 0.15 | 0.10 |

Unit:mm

TABLE II. PERFORMANCE RATINGS:

| Model | Marking | V_{max} (Vdc) | I_{max} (A) | I_{hold} @25°C (A) | I_{trip} @25°C (A) | P_d Typ. (W) | Maximum Time To Trip | | Resistance | |
|---------|------------|--------------------|------------------|----------------------------|----------------------------|----------------------|----------------------|---------------|-------------------------------|-------------------------------|
| | | | | | | | Current (A) | Time (Sec) | $R_{i_{min}}$ (Ω) | $R_{1_{max}}$ (Ω) |
| nSMD025 | αA | 16.0 | 100 | 0.25 | 0.50 | 0.6 | 8.0 | 0.08 | 0.350 | 2.500 |

Order Information

Packaging

| SMD1206 | 025 | Tape & Reel Quantity | |
|---------------------------|---------|----------------------|---------------|
| Product name | Hold | Max | 5000 pcs/reel |
| Size 3216 mm / 1206 mils | Current | voltage | |
| SMD: surface mount device | 0.25A | | |

Recognitio UL Approved.

E201504/E319079



单击下面可查看定价，库存，交付和生命周期等信息

[>>SEA-LAND\(台湾陆海\)](#)